

Unittest for caching

March 23, 2025

Contents

1	Test Information	3
1.1	Test Candidate Information	3
1.2	Unittest Information	3
1.3	Test System Information	3
2	Statistic	3
2.1	Test-Statistic for testrun with python 3.11.2 (final)	3
2.2	Coverage Statistic	4
3	Tested Requirements	5
3.1	Cache generation (json /pickle)	5
3.1.1	Data generation from source instance, if no cache is available	5
3.1.2	Create complete cache from the given data instance	6
3.1.3	Create cache partially from a given data instance by get method	6
3.1.4	Ignore corrupt cache file	7
3.2	Load spreading for full update	8
3.2.1	Full update with delay between each data generation for the cache	8
3.2.2	No cache generation if disabled	8
3.3	Dump cache conditions	9
3.3.1	Dump cache if time is expired	9
3.3.2	Dump cache if data version increases	10
3.3.3	Dump cache if data uid is changed	11
3.3.4	Dump cache if storage version is changed	12
3.3.5	Dump cache if stored value is 'None'	13
3.4	Definition of uncached data	14
3.4.1	Define uncached data	14
3.5	Callback on data storage	15
3.5.1	If no data is changed, no callback will be executed	15
3.5.2	Callback execution in case of a full update	15
3.5.3	Callback execution in case of get function	16

A	Trace for testrun with python 3.11.2 (final)	17
A.1	Tests with status Info (15)	17
A.1.1	REQ-0003	17
A.1.2	REQ-0001	18
A.1.3	REQ-0005	20
A.1.4	REQ-0015	22
A.1.5	REQ-0004	22
A.1.6	REQ-0002	23
A.1.7	REQ-0006	24
A.1.8	REQ-0007	27
A.1.9	REQ-0008	29
A.1.10	REQ-0009	31
A.1.11	REQ-0014	33
A.1.12	REQ-0010	35
A.1.13	REQ-0011	36
A.1.14	REQ-0012	37
A.1.15	REQ-0013	37
B	Test-Coverage	38
B.1	caching	38
B.1.1	caching.__init__.py	38

1 Test Information

1.1 Test Candidate Information

The Module `caching` is designed to store information in `json` or `pickle` files to support them much faster then generating them from the original source file. For more Information read the documentation.

Library Information	
Name	caching
State	Released
Supported Interpreters	python3
Version	da3d2c10abaf6d290e5d8087bf6bc170

Dependencies	
--------------	--

1.2 Unittest Information

Unittest Information	
Version	17bb378e039385c5fbedba201e1a6df9
Testruns with	python 3.11.2 (final)

1.3 Test System Information

System Information	
Architecture	64bit
Distribution	Debian GNU/Linux 12 bookworm
Hostname	ahorn
Kernel	6.1.0-17-amd64 (#1 SMP PREEMPT_DYNAMIC Debian 6.1.69-1 (2023-12-30))
Machine	x86_64
Path	/home/dirk/my_repositories/unittest/caching
System	Linux
Username	dirk

2 Statistic

2.1 Test-Statistic for testrun with python 3.11.2 (final)

Number of tests	15
Number of successfull tests	15
Number of possibly failed tests	0
Number of failed tests	0

Executionlevel	Full Test (all defined tests)
Time consumption	8.066s

2.2 Coverage Statistic

Module- or Filename	Line-Coverage	Branch-Coverage
caching	97.3%	96.4%
caching.__init__.py	97.3%	

3 Tested Requirements

3.1 Cache generation (json /pickle)

3.1.1 Data generation from source instance, if no cache is available

Description

If the cache is not available, the data shall be generated from the source instance.

Reason for the implementation

There shall be the possibility to create the cache on demand, so the fallback is to generate the data from the source instance.

Fitcriterion

Caching is called without previous cache generation and the data from the source instance is completely available.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.1!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:24,028
Finished-Time:	2025-03-23 16:02:24,030
Time-Consumption	0.002s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content '.__string__' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content '.__unicode__' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).
Success	Data from cached instance with key=unknown_key is correct (Content 5 and Type is <class 'int'>).

3.1.2 Create complete cache from the given data instance

Description

There shall be a method caching all information from the given instance.

Reason for the implementation

Independent usage of data generation and data usage (e.g. the user requesting the data is not able to create the data).

Fitcriterion

Caching is called twice with different data instances and the cached data from the first call is completely available.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.2!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_...init....py (327)
Start-Time:	2025-03-23 16:02:24,030
Finished-Time:	2025-03-23 16:02:24,033
Time-Consumption	0.003s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_pickle' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).
Success	Data from cached instance with key=unknown_key is correct (Content 5 and Type is <class 'int'>).

3.1.3 Create cache partially from a given data instance by get method

Description

On getting data from the cached instance, the information shall be stored in the cache file.

Reason for the implementation

There shall be the possibility to create the cache on demand, so the fallback is to generate the data from the source instance.

Fitcriterion

Caching is called twice with different data instances and the cached data from the first call is available for all keys cached on the first run.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.3!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:24,034
Finished-Time:	2025-03-23 16:02:24,038
Time-Consumption	0.005s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content '...unicode...' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).
Success	Data from cached instance with key=unknown_key is correct (Content 5 and Type is <class 'int'>).

3.1.4 Ignore corrupt cache file

Description

Ignore corrupt cachefile, while loading cache.

Reason for the implementation

Suppress exceptions while caching.

Fitcriterion

Loading cache results in no exception, when cache file is empty.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.4!

Testrun:	python 3.11.2 (final)
----------	-----------------------

Caller: /home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
 Start-Time: 2025-03-23 16:02:24,039
 Finished-Time: 2025-03-23 16:02:24,040
 Time-Consumption 0.002s

Testsummary:

Info Prepare: Cleanup before testcase execution
Info Creating empty cache file /home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_corrupt_cache.json.
Success Empty cache file ignored on loading cache.

3.2 Load spreading for full update

3.2.1 Full update with delay between each data generation for the cache

Description

The full update method shall pause for a given time between every cached item.

Reason for the implementation

Load spreading in case of cyclic called `.full_update()`.

Fitcriterion

The time consumption of the method `.full_update(<sleep_time>)` shall consume n times the given `sleep_time`. Where n is the number of items which will be cached from the source instance.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.5!

Testrun: python 3.11.2 (final)
 Caller: /home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
 Start-Time: 2025-03-23 16:02:24,041
 Finished-Time: 2025-03-23 16:02:30,046
 Time-Consumption 6.005s

Testsummary:

Info Prepare: Cleanup before testcase execution
Success Consumed time for full_update is greater expectation (Content 6.003138542175293 and Type is <class 'float'>).
Success Consumed time for full_update is greater expectation (Content 6.003138542175293 and Type is <class 'float'>).

3.2.2 No cache generation if disabled

Description

The cache shall be generated by the `.get()` method, only if the cache instance parameter `store_on_get` is set to `True`.

Reason for the implementation

Independent usage of data generation and data usage (e.g. the user requesting the data is not able to create the data).

Fitcriterion

Create a caching instance with `store_on_get` set to `False`. Get every item of the source instance with the `.get()` method and check that no cache file exists.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.6!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:30,047
Finished-Time:	2025-03-23 16:02:30,059
Time-Consumption	0.012s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Success	Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).
Success	Data from cached instance with key=none is correct (Content None and Type is <class 'NoneType'>).
Success	The cache file (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_full_update_sleep.json) shall not exist is correct (Content False and Type is <class 'bool'>).

3.3 Dump cache conditions

3.3.1 Dump cache if time is expired

Description

Dump the cached item, if this item is older then the given expiry time.

Reason for the implementation

Ensure, that the cache is updated from time to time. For example for items which do not change very often.

Fitcriterion

Create a cache instance, cache some data. Intialise a second caching instance with a different source instance and a

expire time. Wait for longer than the given expiry time and check that the items from the second source instance are returned.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.7!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:30,059
Finished-Time:	2025-03-23 16:02:32,073
Time-Consumption	2.014s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).
Success	Data from cached instance with key=str is correct (Content '.__string__' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content '.__unicode__' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

3.3.2 Dump cache if data version increases

Description

Dump the complete cache, if the *data version* of the source instance is increased.

Reason for the implementation

The data version is part of the source instance. Increasing the data version indicates, that the source instance generates

the data in another way or the structure of the data is changed. In that condition, the cache needs to be ignored.

Fitcriterion

Create a cached instance and cache some items. Generate a second cached instance with different source data and a increased data version. Ensure, that the cache instance returns the values from the second source. It is required to set `load_all_on_init` to `False` and `store_on_get` to `True`.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.8!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,073
Finished-Time:	2025-03-23 16:02:32,077
Time-Consumption	0.004s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content '.__string__' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content '.__unicode__' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

3.3.3 Dump cache if data uid is changed

Description

Dump the complete cache, if the *data uid* of the source instance is changed.

Reason for the implementation

The data uid is part of the source instance. Changing the data uid indicates, that the source of the data created by the source instance is changed (e.g. the uid of a file or folder) and the cache needs to be ignored.

Fitcriterion

Create a cached instance and cache some items. Generate a second cached instance with different source data and a changed data uid. Ensure, that the cache instance returns the values from the second source. It is required to set `load_all_on_init` to `False` and `store_on_get` to `True`.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.9!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,078
Finished-Time:	2025-03-23 16:02:32,082
Time-Consumption	0.004s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content '.__string__' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content '.__unicode__' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

3.3.4 Dump cache if storage version is changed

Description

Dump the complete cache, if the *storage version* of the caching class is changed.

Reason for the implementation

The storage version is part of the caching class. Changing the storage version indicates, that the previously stored cache is not compatible due to new data storage and the cache needs to be ignored.

Fitcriterion

Create a cached instance and cache some items. Generate a second cached instance with different source data and a changed storage version. Ensure, that the cache instance returns the values from the second source. It is required to set `load_all_on_init` to `False` and `store_on_get` to `True`.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.10!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,082
Finished-Time:	2025-03-23 16:02:32,086

Time-Consumption 0.004s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content '.__string__' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content '.__unicode__' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).
Success	Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).
Success	Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

3.3.5 Dump cache if stored value is 'None'

Description

Dump the cached item, if the stored value is None.

Reason for the implementation

If no information is stored in the cache, the data shall be generated by the source instance.

Fitcriterion

Create a cached instance and cache some items. One needs to have None as value. Generate a second cached instance with different source data (especially, the previous item with value None needs to have a not None value. Ensure, that the caching instance returns not None from the second source.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.11!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,087
Finished-Time:	2025-03-23 16:02:32,090
Time-Consumption	0.003s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).

Success Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).

Success Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).

Success Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

Success Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

3.4 Definition of uncached data

3.4.1 Define uncached data

Description

It shall be possible to define items which are not cached.

Reason for the implementation

If there is dynamic changed data in the source instance, it shall be possible to define these items as non cached to get them always from the source instance.

Fitcriterion

Create a cached instance and cache some items. Generate a second cached instance with different source data and set at least one item as source item. This item should be previously cached. Ensure, that the source item is the one from the second source instance.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.12!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,090
Finished-Time:	2025-03-23 16:02:32,094
Time-Consumption	0.003s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Prepare: First usage of 'property_cache_json' with a class holding the data to be cached
Success	Data from cached instance with key=str is correct (Content '.__string__' and Type is <class 'str'>).
Success	Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).
Success	Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).
Success	Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).
Success	Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

Success Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).

3.5 Callback on data storage

3.5.1 If no data is changed, no callback will be executed

Description

The store callback shall not be executed, if no cache is stored.

Reason for the implementation

Do actions, if cache data is stored to disk.

Fitcriterion

Initialise the cache instance without storing cache data. Ensure, that the callback is never executed.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.13!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,094
Finished-Time:	2025-03-23 16:02:32,094
Time-Consumption	0.000s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Installing save_callback with no get or full_update execution.
Success	Save callback execution counter is correct (Content 0 and Type is <class 'int'>).
Success	Save callback execution counter is correct (Content None and Type is <class 'NoneType'>).

3.5.2 Callback execution in case of a full update

Description

The storage callback shall be called once on every full_update().

Reason for the implementation

Do actions, if cache data is stored to disk.

Fitcriterion

Initialise the cache instance and ensure, that the callback is executed as often as the .full_update() method is executed.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.14!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,094
Finished-Time:	2025-03-23 16:02:32,096
Time-Consumption	0.001s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Installing save_callback and execute full_update.
Success	Save callback execution counter is correct (Content 1 and Type is <class 'int'>).
Success	Save callback execution counter is correct (Content <caching.property_cache_json object at 0x7fbf8f308290> and Type is <class 'caching.property_cache_json'>).

3.5.3 Callback execution in case of get function

Description

The storage callback, shall be called once on every `.get()`, if `storage.on_get` is set to `True`.

Reason for the implementation

Do actions, if cache data is stored to disk.

Fitcriterion

Initialise the cache instance and ensure, that the callback is executed as often as the `.get()` method is executed.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.15!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/caching/unittest/src/report/_init_.py (327)
Start-Time:	2025-03-23 16:02:32,096
Finished-Time:	2025-03-23 16:02:32,097
Time-Consumption	0.002s

Testsummary:

Info	Prepare: Cleanup before testcase execution
Info	Installing save_callback and execute a single get.
Info	Installing save_callback and execute a single get.
Success	Save callback execution counter is correct (Content 2 and Type is <class 'int'>).
Success	Save callback execution counter is correct (Content <caching.property_cache_json object at 0x7fbf8f308f90> and Type is <class 'caching.property_cache_json'>).

A Trace for testrun with python 3.11.2 (final)

A.1 Tests with status Info (15)

A.1.1 REQ-0003

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

Success Data from cached instance with key=str is correct (Content '__string__' and Type is <class 'str'>).

Cache file does not exists (yet).

Loading property for key='str' from source instance

Result (Data from cached instance with key=str): '__string__' (<class 'str'>)

Expectation (Data from cached instance with key=str): result = '__string__' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content '__unicode__' and Type is <class 'str'>).

Loading property for key='unicode' from source instance

Result (Data from cached instance with key=unicode): '__unicode__' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = '__unicode__' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).

Loading property for key='integer' from source instance

Result (Data from cached instance with key=integer): 34 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 34 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).

Loading property for key='float' from source instance

Result (Data from cached instance with key=float): 2.71828 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 2.71828 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).

Loading property for key='list' from source instance

Result (Data from cached instance with key=list): ['one', 2, 3, '4'] (<class 'list'>)

```
Expectation (Data from cached instance with key=list): result = [ 'one', 2, 3, '4' ] (<class 'list'>)
```

Success Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).

```
Loading property for key='dict' from source instance
```

```
Result (Data from cached instance with key=dict): { '1': '1', '2': 2, '3': 'three', '4': '4' } (<class 'dict'>)
```

```
Expectation (Data from cached instance with key=dict): result = { '1': '1', '2': 2, '3': 'three', '4': '4' } (<class 'dict'>)
```

Success Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

```
Loading property for key='none' from source instance
```

```
Result (Data from cached instance with key=none): 'not None' (<class 'str'>)
```

```
Expectation (Data from cached instance with key=none): result = 'not None' (<class 'str'>)
```

Success Data from cached instance with key=unknown_key is correct (Content 5 and Type is <class 'int'>).

```
Key 'unknown_key' is not in cached_keys. Uncached data will be returned.
```

```
Result (Data from cached instance with key=unknown_key): 5 (<class 'int'>)
```

```
Expectation (Data from cached instance with key=unknown_key): result = 5 (<class 'int'>)
```

A.1.2 REQ-0001

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.pickle' with a class holding the data to be cached

```
Cache file does not exists (yet).
```

```
Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_load_on_init.pkl)
```

Success Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).

```
Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_load_on_init.pkl)
```

```
Providing property for 'str' from cache
```

```
Result (Data from cached instance with key=str): 'string' (<class 'str'>)
```

Expectation (Data from cached instance with key=str): result = 'string' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).

Providing property for 'unicode' from cache

Result (Data from cached instance with key=unicode): 'unicode' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = 'unicode' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).

Providing property for 'integer' from cache

Result (Data from cached instance with key=integer): 17 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 17 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).

Providing property for 'float' from cache

Result (Data from cached instance with key=float): 3.14159 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 3.14159 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

Providing property for 'list' from cache

Result (Data from cached instance with key=list): [1, 'two', '3', 4] (<class 'list'>)

Expectation (Data from cached instance with key=list): result = [1, 'two', '3', 4] (<class 'list'>)

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

Providing property for 'dict' from cache

Result (Data from cached instance with key=dict): { '1': 1, '2': 'two', '3': '3', '4': 4 } (<class 'dict'>)

Expectation (Data from cached instance with key=dict): result = { '1': 1, '2': 'two', '3': '3', '4': 4 } (<class 'dict'>)

Success Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).

Providing property for 'none' from cache

Result (Data from cached instance with key=None): None (<class 'NoneType'>)

Expectation (Data from cached instance with key=None): result = None (<class 'NoneType'>)

Success Data from cached instance with key=unknown_key is correct (Content 5 and Type is <class 'int'>).

Key 'unknown_key' is not in cached_keys. Uncached data will be returned.

Result (Data from cached instance with key=unknown_key): 5 (<class 'int'>)

Expectation (Data from cached instance with key=unknown_key): result = 5 (<class 'int'>)

A.1.3 REQ-0005

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Cache file does not exist on filesystem.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

Cache file does not exists (yet).

Loading property for key='str' from source instance

Adding key=str, value=string with timestamp=1742742144 to cache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/cache_data_test_load_on_init.json
 ↳ a_test_load_on_init.json)

Loading property for key='integer' from source instance

Adding key=integer, value=17 with timestamp=1742742144 to cache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/cache_data_test_load_on_init.json
 ↳ a_test_load_on_init.json)

Loading property for key='list' from source instance

Adding key=list, value=[1, 'two', '3', 4] with timestamp=1742742144 to cache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/cache_data_test_load_on_init.json
 ↳ a_test_load_on_init.json)

Loading property for key='dict' from source instance

Adding key=dict, value={'1': 1, '2': 'two', '3': '3', '4': 4} with timestamp=1742742144 to cache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/cache_data_test_load_on_init.json
 ↳ a_test_load_on_init.json)

Loading property for key='none' from source instance

Adding key=none, value=None with timestamp=1742742144 to cache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/cache_data_test_load_on_init.json
 ↳ a_test_load_on_init.json)

Success Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).

Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/cache_data_test_load_on_init.json
 ↳ ta/cache_data_test_load_on_init.json)

Providing property for 'str' from cache

Result (Data from cached instance with key=str): 'string' (<class 'str'>)

Expectation (Data from cached instance with key=str): result = 'string' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content '__unicode__' and Type is <class 'str'>).

Loading property for key='unicode' from source instance

Unittest for caching

```
Adding key=unicode, value=__unicode__ with timestamp=1742742144 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_load_on_init.json)
Result (Data from cached instance with key=unicode): '__unicode__' (<class 'str'>)
Expectation (Data from cached instance with key=unicode): result = '__unicode__' (<class
↳ 'str'>)
```

Success Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).

```
Providing property for 'integer' from cache
Result (Data from cached instance with key=integer): 17 (<class 'int'>)
Expectation (Data from cached instance with key=integer): result = 17 (<class 'int'>)
```

Success Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).

```
Loading property for key='float' from source instance
Adding key=float, value=2.71828 with timestamp=1742742144 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_load_on_init.json)
Result (Data from cached instance with key=float): 2.71828 (<class 'float'>)
Expectation (Data from cached instance with key=float): result = 2.71828 (<class 'float'>)
```

Success Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

```
Providing property for 'list' from cache
Result (Data from cached instance with key=list): [ 1, 'two', '3', 4 ] (<class 'list'>)
Expectation (Data from cached instance with key=list): result = [ 1, 'two', '3', 4 ] (<class
↳ 'list'>)
```

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

```
Providing property for 'dict' from cache
Result (Data from cached instance with key=dict): { '1': 1, '2': 'two', '3': '3', '4': 4 }
↳ (<class 'dict'>)
Expectation (Data from cached instance with key=dict): result = { '1': 1, '2': 'two', '3':
↳ '3', '4': 4 } (<class 'dict'>)
```

Success Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).

```
Providing property for 'none' from cache
Result (Data from cached instance with key=None): None (<class 'NoneType'>)
Expectation (Data from cached instance with key=None): result = None (<class 'NoneType'>)
```

Success Data from cached instance with key=unknown_key is correct (Content 5 and Type is <class 'int'>).

```
Key 'unknown_key' is not in cached_keys. Uncached data will be returned.
Result (Data from cached instance with key=unknown_key): 5 (<class 'int'>)
Expectation (Data from cached instance with key=unknown_key): result = 5 (<class 'int'>)
```

A.1.4 REQ-0015

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Creating empty cache file /home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_corrupt_cache.json.

Success Empty cache file ignored on loading cache.

Exception while loading cache file /home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_corrupt_cache.json
 ↳ t_data/cache_data_test_corrupt_cache.json

A.1.5 REQ-0004

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Cache file does not exist on filesystem.

Success Consumed time for full_update is greater expectation (Content 6.003138542175293 and Type is <class 'float'>).

Cache file does not exists (yet).

Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']

Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_full_update_sleep.json)
 ↳ a_test_full_update_sleep.json

Result (Consumed time for full_update): 6.003138542175293 (<class 'float'>)

Expectation (Consumed time for full_update): result > 6.0 (<class 'float'>)

Success Consumed time for full_update is greater expectation (Content 6.003138542175293 and Type is <class 'float'>).

Result (Consumed time for full_update): 6.003138542175293 (<class 'float'>)

Expectation (Consumed time for full_update): result < 6.5 (<class 'float'>)

A.1.6 REQ-0002

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Success Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).

Cache file does not exists (yet).

Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']

Providing property for 'str' from cache

Result (Data from cached instance with key=str): 'string' (<class 'str'>)

Expectation (Data from cached instance with key=str): result = 'string' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).

Providing property for 'unicode' from cache

Result (Data from cached instance with key=unicode): 'unicode' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = 'unicode' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).

Providing property for 'integer' from cache

Result (Data from cached instance with key=integer): 17 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 17 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).

Providing property for 'float' from cache

Result (Data from cached instance with key=float): 3.14159 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 3.14159 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

Providing property for 'list' from cache

Result (Data from cached instance with key=list): [1, 'two', '3', 4] (<class 'list'>)

Expectation (Data from cached instance with key=list): result = [1, 'two', '3', 4] (<class 'list'>)

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

Providing property for 'dict' from cache

Unittest for caching

```
Result (Data from cached instance with key=dict): { '1': 1, '2': 'two', '3': '3', '4': 4 }  
↳ (<class 'dict'>)
```

```
Expectation (Data from cached instance with key=dict): result = { '1': 1, '2': 'two', '3':  
↳ '3', '4': 4 } (<class 'dict'>)
```

Success Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).

Providing property for 'None' from cache

```
Result (Data from cached instance with key=None): None (<class 'NoneType'>)
```

```
Expectation (Data from cached instance with key=None): result = None (<class 'NoneType'>)
```

Success The cache file (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_full_update_sleep.json) shall not exist is correct (Content False and Type is <class 'bool'>).

```
Result (The cache file (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_full_update_sleep.json) shall not exist): False (<class 'bool'>)
```

```
Expectation (The cache file (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_full_update_sleep.json) shall not exist): result = False (<class 'bool'>)
```

A.1.7 REQ-0006

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

Cache file does not exist (yet).

```
Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']  
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)  
↳ a_test_dump_cache.json)
```

Success Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).

```
Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)  
↳ ta/cache_data_test_dump_cache.json)
```

Providing property for 'str' from cache

```
Result (Data from cached instance with key=str): 'string' (<class 'str'>)
```

```
Expectation (Data from cached instance with key=str): result = 'string' (<class 'str'>)
```

Success Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).

Providing property for 'unicode' from cache

Result (Data from cached instance with key=unicode): 'unicode' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = 'unicode' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).

Providing property for 'integer' from cache

Result (Data from cached instance with key=integer): 17 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 17 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).

Providing property for 'float' from cache

Result (Data from cached instance with key=float): 3.14159 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 3.14159 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

Providing property for 'list' from cache

Result (Data from cached instance with key=list): [1, 'two', '3', 4] (<class 'list'>)

Expectation (Data from cached instance with key=list): result = [1, 'two', '3', 4] (<class 'list'>)

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

Providing property for 'dict' from cache

Result (Data from cached instance with key=dict): { '1': 1, '2': 'two', '3': '3', '4': 4 } (<class 'dict'>)

Expectation (Data from cached instance with key=dict): result = { '1': 1, '2': 'two', '3': '3', '4': 4 } (<class 'dict'>)

Success Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).

Providing property for 'None' from cache

Result (Data from cached instance with key=None): None (<class 'NoneType'>)

Expectation (Data from cached instance with key=None): result = None (<class 'NoneType'>)

Success Data from cached instance with key=str is correct (Content '_string_' and Type is <class 'str'>).

The cached value is old, cached value will be ignored

Loading property for key='str' from source instance

Unittest for caching

```
Adding key=str, value=__string__ with timestamp=1742742152 to cache
```

```
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data)
↳ a_test_dump_cache.json
```

```
Result (Data from cached instance with key=str): '__string__' (<class 'str'>)
```

```
Expectation (Data from cached instance with key=str): result = '__string__' (<class 'str'>)
```

Success Data from cached instance with key=unicode is correct (Content '__unicode__' and Type is <class 'str'>).

```
The cached value is old, cached value will be ignored
```

```
Loading property for key='unicode' from source instance
```

```
Adding key=unicode, value=__unicode__ with timestamp=1742742152 to cache
```

```
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data)
↳ a_test_dump_cache.json
```

```
Result (Data from cached instance with key=unicode): '__unicode__' (<class 'str'>)
```

```
Expectation (Data from cached instance with key=unicode): result = '__unicode__' (<class 'str'>)
```

Success Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).

```
The cached value is old, cached value will be ignored
```

```
Loading property for key='integer' from source instance
```

```
Adding key=integer, value=34 with timestamp=1742742152 to cache
```

```
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data)
↳ a_test_dump_cache.json
```

```
Result (Data from cached instance with key=integer): 34 (<class 'int'>)
```

```
Expectation (Data from cached instance with key=integer): result = 34 (<class 'int'>)
```

Success Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).

```
The cached value is old, cached value will be ignored
```

```
Loading property for key='float' from source instance
```

```
Adding key=float, value=2.71828 with timestamp=1742742152 to cache
```

```
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data)
↳ a_test_dump_cache.json
```

```
Result (Data from cached instance with key=float): 2.71828 (<class 'float'>)
```

```
Expectation (Data from cached instance with key=float): result = 2.71828 (<class 'float'>)
```

Success Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).

```
The cached value is old, cached value will be ignored
```

```
Loading property for key='list' from source instance
```

```
Adding key=list, value=['one', 2, 3, '4'] with timestamp=1742742152 to cache
```

```
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data)
↳ a_test_dump_cache.json
```

Result (Data from cached instance with key=list): ['one', 2, 3, '4'] (<class 'list'>)

Expectation (Data from cached instance with key=list): result = ['one', 2, 3, '4'] (<class 'list'>)

Success Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).

The cached value is old, cached value will be ignored

Loading property for key='dict' from source instance

Adding key=dict, value={'1': '1', '2': 2, '3': 'three', '4': '4'} with timestamp=1742742152
 ↳ to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_a_test_dump_cache.json)

Result (Data from cached instance with key=dict): { '1': '1', '2': 2, '3': 'three', '4': '4' } (<class 'dict'>)

Expectation (Data from cached instance with key=dict): result = { '1': '1', '2': 2, '3': 'three', '4': '4' } (<class 'dict'>)

Success Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

The cached value is old, cached value will be ignored

Loading property for key='None' from source instance

Adding key=None, value=not None with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_a_test_dump_cache.json)

Result (Data from cached instance with key=None): 'not None' (<class 'str'>)

Expectation (Data from cached instance with key=None): result = 'not None' (<class 'str'>)

A.1.8 REQ-0007

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

Cache file does not exists (yet).

Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_a_test_dump_cache.json)

Success Data from cached instance with key=str is correct (Content '__string__' and Type is <class 'str'>).

Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/ta/cache_data_test_dump_cache.json)
 ↳ ta/cache_data_test_dump_cache.json)

Data version increased, ignoring previous cache data

Loading property for key='str' from source instance

Adding key=str, value=__string__ with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/ta_test_dump_cache.json)
 ↳ a_test_dump_cache.json)

Result (Data from cached instance with key=str): '__string__' (<class 'str'>)

Expectation (Data from cached instance with key=str): result = '__string__' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content '__unicode__' and Type is <class 'str'>).

Loading property for key='unicode' from source instance

Adding key=unicode, value=__unicode__ with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/ta_test_dump_cache.json)
 ↳ a_test_dump_cache.json)

Result (Data from cached instance with key=unicode): '__unicode__' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = '__unicode__' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).

Loading property for key='integer' from source instance

Adding key=integer, value=34 with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/ta_test_dump_cache.json)
 ↳ a_test_dump_cache.json)

Result (Data from cached instance with key=integer): 34 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 34 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).

Loading property for key='float' from source instance

Adding key=float, value=2.71828 with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/ta_test_dump_cache.json)
 ↳ a_test_dump_cache.json)

Result (Data from cached instance with key=float): 2.71828 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 2.71828 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).

Loading property for key='list' from source instance

```
Adding key=list, value=['one', 2, 3, '4'] with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
Result (Data from cached instance with key=list): [ 'one', 2, 3, '4' ] (<class 'list'>)
Expectation (Data from cached instance with key=list): result = [ 'one', 2, 3, '4' ] (<class
↪ 'list'>)
```

Success Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).

```
Loading property for key='dict' from source instance
Adding key=dict, value={'1': '1', '2': 2, '3': 'three', '4': '4'} with timestamp=1742742152
↪ to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
Result (Data from cached instance with key=dict): { '1': '1', '2': 2, '3': 'three', '4': '4'
↪ } (<class 'dict'>)
Expectation (Data from cached instance with key=dict): result = { '1': '1', '2': 2, '3':
↪ 'three', '4': '4' } (<class 'dict'>)
```

Success Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

```
Loading property for key='none' from source instance
Adding key=none, value=not None with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
Result (Data from cached instance with key=none): 'not None' (<class 'str'>)
Expectation (Data from cached instance with key=none): result = 'not None' (<class 'str'>)
```

A.1.9 REQ-0008

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

```
Cache file does not exists (yet).
Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
```

Success Data from cached instance with key=str is correct (Content '__string__' and Type is <class 'str'>).

Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/ta/cache_data_test_dump_cache.json)
 ↪ ta/cache_data_test_dump_cache.json)

Source uid changed, ignoring previous cache data

Loading property for key='str' from source instance

Adding key=str, value=__string__ with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=str): '__string__' (<class 'str'>)

Expectation (Data from cached instance with key=str): result = '__string__' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content '__unicode__' and Type is <class 'str'>).

Loading property for key='unicode' from source instance

Adding key=unicode, value=__unicode__ with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=unicode): '__unicode__' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = '__unicode__' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).

Loading property for key='integer' from source instance

Adding key=integer, value=34 with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=integer): 34 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 34 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).

Loading property for key='float' from source instance

Adding key=float, value=2.71828 with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=float): 2.71828 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 2.71828 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).

Loading property for key='list' from source instance

```
Adding key=list, value=['one', 2, 3, '4'] with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_dump_cache.json)
Result (Data from cached instance with key=list): [ 'one', 2, 3, '4' ] (<class 'list'>)
Expectation (Data from cached instance with key=list): result = [ 'one', 2, 3, '4' ] (<class
↳ 'list'>)
```

Success Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).

```
Loading property for key='dict' from source instance
Adding key=dict, value={'1': '1', '2': 2, '3': 'three', '4': '4'} with timestamp=1742742152
↳ to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_dump_cache.json)
Result (Data from cached instance with key=dict): { '1': '1', '2': 2, '3': 'three', '4': '4'
↳ } (<class 'dict'>)
Expectation (Data from cached instance with key=dict): result = { '1': '1', '2': 2, '3':
↳ 'three', '4': '4' } (<class 'dict'>)
```

Success Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

```
Loading property for key='none' from source instance
Adding key=None, value=not None with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_dump_cache.json)
Result (Data from cached instance with key=None): 'not None' (<class 'str'>)
Expectation (Data from cached instance with key=None): result = 'not None' (<class 'str'>)
```

A.1.10 REQ-0009

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

```
Cache file does not exists (yet).
Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_dump_cache.json)
```

Success Data from cached instance with key=str is correct (Content '__string__' and Type is <class 'str'>).

Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/ta/cache_data_test_dump_cache.json)
 ↪ ta/cache_data_test_dump_cache.json)

Storage version changed, ignoring previous cache data

Loading property for key='str' from source instance

Adding key=str, value=__string__ with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=str): '__string__' (<class 'str'>)

Expectation (Data from cached instance with key=str): result = '__string__' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content '__unicode__' and Type is <class 'str'>).

Loading property for key='unicode' from source instance

Adding key=unicode, value=__unicode__ with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=unicode): '__unicode__' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = '__unicode__' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 34 and Type is <class 'int'>).

Loading property for key='integer' from source instance

Adding key=integer, value=34 with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=integer): 34 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 34 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).

Loading property for key='float' from source instance

Adding key=float, value=2.71828 with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↪ a_test_dump_cache.json)

Result (Data from cached instance with key=float): 2.71828 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 2.71828 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content ['one', 2, 3, '4'] and Type is <class 'list'>).

Loading property for key='list' from source instance

```
Adding key=list, value=['one', 2, 3, '4'] with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
Result (Data from cached instance with key=list): [ 'one', 2, 3, '4' ] (<class 'list'>)
Expectation (Data from cached instance with key=list): result = [ 'one', 2, 3, '4' ] (<class
↪ 'list'>)
```

Success Data from cached instance with key=dict is correct (Content {'1': '1', '2': 2, '3': 'three', '4': '4'} and Type is <class 'dict'>).

```
Loading property for key='dict' from source instance
Adding key=dict, value={'1': '1', '2': 2, '3': 'three', '4': '4'} with timestamp=1742742152
↪ to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
Result (Data from cached instance with key=dict): { '1': '1', '2': 2, '3': 'three', '4': '4'
↪ } (<class 'dict'>)
Expectation (Data from cached instance with key=dict): result = { '1': '1', '2': 2, '3':
↪ 'three', '4': '4' } (<class 'dict'>)
```

Success Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

```
Loading property for key='none' from source instance
Adding key=None, value=not None with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
Result (Data from cached instance with key=None): 'not None' (<class 'str'>)
Expectation (Data from cached instance with key=None): result = 'not None' (<class 'str'>)
```

A.1.11 REQ-0014

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

```
Cache file does not exists (yet).
Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data
↪ a_test_dump_cache.json)
```

Success Data from cached instance with key=str is correct (Content 'string' and Type is <class 'str'>).

Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data_test_dump_cache.json)
 ↳ ta/cache_data_test_dump_cache.json)

Providing property for 'str' from cache

Result (Data from cached instance with key=str): 'string' (<class 'str'>)

Expectation (Data from cached instance with key=str): result = 'string' (<class 'str'>)

Success Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).

Providing property for 'unicode' from cache

Result (Data from cached instance with key=unicode): 'unicode' (<class 'str'>)

Expectation (Data from cached instance with key=unicode): result = 'unicode' (<class 'str'>)

Success Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).

Providing property for 'integer' from cache

Result (Data from cached instance with key=integer): 17 (<class 'int'>)

Expectation (Data from cached instance with key=integer): result = 17 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 3.14159 and Type is <class 'float'>).

Providing property for 'float' from cache

Result (Data from cached instance with key=float): 3.14159 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 3.14159 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

Providing property for 'list' from cache

Result (Data from cached instance with key=list): [1, 'two', '3', 4] (<class 'list'>)

Expectation (Data from cached instance with key=list): result = [1, 'two', '3', 4] (<class 'list'>)
 ↳ 'list'>)

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

Providing property for 'dict' from cache

Result (Data from cached instance with key=dict): { '1': 1, '2': 'two', '3': '3', '4': 4 }
 ↳ (<class 'dict'>)

Expectation (Data from cached instance with key=dict): result = { '1': 1, '2': 'two', '3': '3', '4': 4 } (<class 'dict'>)
 ↳ '3', '4': 4 } (<class 'dict'>)

Success Data from cached instance with key=None is correct (Content 'not None' and Type is <class 'str'>).

Providing property for 'None' from cache

```

Loading property for key='none' from source instance
Adding key=none, value=not None with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_dump_cache.json)
Result (Data from cached instance with key=none): 'not None' (<class 'str'>)
Expectation (Data from cached instance with key=none): result = 'not None' (<class 'str'>)
    
```

A.1.12 REQ-0010

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Prepare: First usage of 'property_cache.json' with a class holding the data to be cached

```

Cache file does not exists (yet).
Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']
Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_source_key_def.json)
    
```

Success Data from cached instance with key=str is correct (Content '__string__' and Type is <class 'str'>).

```

Loading properties from cache (/home/dirk/my_repositories/unittest/caching/unittest/output_data/
↳ ta/cache_data_test_source_key_def.json)
Loading property for key='str' from source instance
Adding key=str, value=__string__ with timestamp=1742742152 to chache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/
↳ a_test_source_key_def.json)
Result (Data from cached instance with key=str): '__string__' (<class 'str'>)
Expectation (Data from cached instance with key=str): result = '__string__' (<class 'str'>)
    
```

Success Data from cached instance with key=unicode is correct (Content 'unicode' and Type is <class 'str'>).

```

Providing property for 'unicode' from cache
Result (Data from cached instance with key=unicode): 'unicode' (<class 'str'>)
Expectation (Data from cached instance with key=unicode): result = 'unicode' (<class 'str'>)
    
```

Success Data from cached instance with key=integer is correct (Content 17 and Type is <class 'int'>).

```

Providing property for 'integer' from cache
Result (Data from cached instance with key=integer): 17 (<class 'int'>)
    
```

Expectation (Data from cached instance with key=integer): result = 17 (<class 'int'>)

Success Data from cached instance with key=float is correct (Content 2.71828 and Type is <class 'float'>).

Loading property for key='float' from source instance

Adding key=float, value=2.71828 with timestamp=1742742152 to chache

cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/cache_data/ → a_test_source_key_def.json)

Result (Data from cached instance with key=float): 2.71828 (<class 'float'>)

Expectation (Data from cached instance with key=float): result = 2.71828 (<class 'float'>)

Success Data from cached instance with key=list is correct (Content [1, 'two', '3', 4] and Type is <class 'list'>).

Providing property for 'list' from cache

Result (Data from cached instance with key=list): [1, 'two', '3', 4] (<class 'list'>)

Expectation (Data from cached instance with key=list): result = [1, 'two', '3', 4] (<class 'list'>)

Success Data from cached instance with key=dict is correct (Content {'1': 1, '2': 'two', '3': '3', '4': 4} and Type is <class 'dict'>).

Providing property for 'dict' from cache

Result (Data from cached instance with key=dict): { '1': 1, '2': 'two', '3': '3', '4': 4 } (<class 'dict'>)

Expectation (Data from cached instance with key=dict): result = { '1': 1, '2': 'two', '3': '3', '4': 4 } (<class 'dict'>)

Success Data from cached instance with key=None is correct (Content None and Type is <class 'NoneType'>).

Providing property for 'none' from cache

Result (Data from cached instance with key=None): None (<class 'NoneType'>)

Expectation (Data from cached instance with key=None): result = None (<class 'NoneType'>)

A.1.13 REQ-0011

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Installing save_callback with no get or full_update execution.

Success Save callback execution counter is correct (Content 0 and Type is <class 'int'>).

Result (Save callback execution counter): 0 (<class 'int'>)

Expectation (Save callback execution counter): result = 0 (<class 'int'>)

Success Save callback execution counter is correct (Content None and Type is <class 'NoneType'>).

Result (Save callback execution counter): None (<class 'NoneType'>)

Expectation (Save callback execution counter): result = None (<class 'NoneType'>)

A.1.14 REQ-0012

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Cache file does not exist on filesystem.

Info Installing save_callback and execute full_update.

Cache file does not exists (yet).

Loading all data from source - ['str', 'unicode', 'integer', 'float', 'list', 'dict', 'none']
 cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/save_call_ ↵
 ↵ back_callback.json)

Success Save callback execution counter is correct (Content 1 and Type is <class 'int'>).

Result (Save callback execution counter): 1 (<class 'int'>)

Expectation (Save callback execution counter): result = 1 (<class 'int'>)

Success Save callback execution counter is correct (Content <caching.property_cache_json object at 0x7fbf8f308290> and Type is <class 'caching.property_cache_json'>).

Result (Save callback execution counter): <caching.property_cache_json object at ↵
 ↵ 0x7fbf8f308290> (<class 'caching.property_cache_json'>)

Expectation (Save callback execution counter): result = <caching.property_cache_json object ↵
 ↵ at 0x7fbf8f308290> (<class 'caching.property_cache_json'>)

A.1.15 REQ-0013

Testresult

This test was passed with the state: **Success**.

Info Prepare: Cleanup before testcase execution

Deleting cache file from filesystem to ensure identical conditions for each test run.

Info Installing save_callback and execute a single get.

Cache file does not exists (yet).

```

Loading property for key='str' from source instance
Adding key=str, value=string with timestamp=1742742152 to cache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/save_call_
↪ back_callback.json)

```

Info Installing save_callback and execute a single get.

```

Loading property for key='unicode' from source instance
Adding key=unicode, value=unicode with timestamp=1742742152 to cache
cache-file stored (/home/dirk/my_repositories/unittest/caching/unittest/output_data/save_call_
↪ back_callback.json)

```

Success Save callback execution counter is correct (Content 2 and Type is <class 'int'>).

```

Result (Save callback execution counter): 2 (<class 'int'>)
Expectation (Save callback execution counter): result = 2 (<class 'int'>)

```

Success Save callback execution counter is correct (Content < caching.property_cache.json object at 0x7fbf8f308f90> and Type is <class 'caching.property_cache.json'>).

```

Result (Save callback execution counter): <caching.property_cache.json object at
↪ 0x7fbf8f308f90> (<class 'caching.property_cache.json'>)
Expectation (Save callback execution counter): result = <caching.property_cache.json object
↪ at 0x7fbf8f308f90> (<class 'caching.property_cache.json'>)

```

B Test-Coverage

B.1 caching

The line coverage for caching was 97.3%
The branch coverage for caching was 96.4%

B.1.1 caching.__init__.py

The line coverage for caching.__init__.py was 97.3%
The branch coverage for caching.__init__.py was 96.4%

```

1 #!/usr/bin/env python
2 # -*- coding: utf-8 -*-
3 #
4 """
5 caching (Caching Module)
6
7
8 **Author:**
9
10 * Dirk Alders <sudo-dirk@mount-mockery.de>
11
12 **Description:**

```

Unittest for caching

```
13
14     This Module supports functions and classes for caching e.g. properties of other instances.
15
16 **Submodules:**
17
18 * :class:`caching.property_cache_json`
19 * :class:`caching.property_cache_pickle`
20
21 **Unittest:**
22
23     See also the :download:`unittest <caching/_testresults_/unittest.pdf>` documentation.
24 """
25 __DEPENDENCIES__ = []
26
27 import json
28 import logging
29 import os
30 import pickle
31 import time
32
33 try:
34     from config import APP_NAME as ROOT_LOGGER_NAME
35 except ImportError:
36     ROOT_LOGGER_NAME = 'root'
37 logger = logging.getLogger(ROOT_LOGGER_NAME).getChild(__name__)
38
39 __DESCRIPTION__ = """The Module {\\tt %s} is designed to store information in {\\tt json} or {\\tt
40     tt pickle} files to support them much faster then generating them from the original source
41     file.
42 For more Information read the documentation.""" % __name__.replace('_', '\\_')
43 """The Module Description"""
44 __INTERPRETER__ = (3, )
45 """The Tested Interpreter—Versions"""
46
47
48 class property_cache_pickle(object):
49     """
50     This class caches the data from a given `source_instance`. It takes the data from the cache
51     instead of generating the data from the `source_instance`,
52     if the conditions for the cache usage are given.
53
54     .. admonition:: Required properties for the `source_instance`
55
56         * **uid():** returns the unique id of the source's source or None, if you don't
57         want to use the unique id.
58         * **keys():** returns a list of all available keys.
59         * **data_version():** returns a version number of the current data (it should be
60         increased, if the get method of the source instance returns improved values or the data
61         structure had been changed).
62         * **get(key, default):** returns the property for a key. If key does not exists,
63         default will be returned.
64
65     :param source_instance: The source instance holding the data
66     :type source_instance: instance
67     :param cache_filename: File name, where the properties are stored as cache
68     :type cache_filename: str
69     :param load_all_on_init: True will load all data from the source instance, when the cache
70     will be initialised the first time.
71     :type load_all_on_init: bool
72     :param callback_on_data_storage: The callback will be executed every time when the cache file
73     is stored. It will be executed with the instance of this class as first argument.
```


Unittest for caching

```
65 :type callback_on_data_storage: method
66 :param max_age: The maximum age of the cached data in seconds or None for no maximum age.
67 :type max_age: int or None
68 :param store_on_get: False will prevent cache storage with execution of the ``.get(key,
69 :type store_on_get: bool
70
71 .. admonition:: The cache will be used, if all following conditions are given
72
73     * The key is in the list returned by ``.keys()`` method of the ``source_instance``
74     * The key is not in the list of keys added by the ``.add_source_get_keys()`` method
75
76     * The cache age is less then the given max_age parameter or the given max_age is
77     None.
78     * The uid of the source instance (e.g. a checksum or unique id of the source) is
79     identically to to uid stored in the cache.
80     * The data version of the ``source_instance`` is <= the data version stored in the
81     cache.
82     * The value is available in the previous stored information
83
84 **Example:**
85
86 .. literalinclude:: caching/_examples_/property_cache_pickle.py
87
88 Will result on the first execution to the following output (with a long execution time):
89
90 .. literalinclude:: caching/_examples_/property_cache_pickle_1.log
91
92 With every following execution the time cosumption my by much smaller:
93
94 .. literalinclude:: caching/_examples_/property_cache_pickle_2.log
95 """
96 DATA_VERSION_TAG = '_property_cache_data_version_'
97 STORAGE_VERSION_TAG = '_storage_version_'
98 UID_TAG = '_property_cache_uid_'
99 DATA_TAG = '_data_'
100 AGE_TAG = '_age_'
101 #
102 STORAGE_VERSION = 1
103
104 def __init__(self, source_instance, cache_filename, load_all_on_init=False,
105 callback_on_data_storage=None, max_age=None, store_on_get=True, return_source_on_none=False):
106     self._source_instance = source_instance
107     self._cache_filename = cache_filename
108     self._load_all_on_init = load_all_on_init
109     self._callback_on_data_storage = callback_on_data_storage
110     self._max_age = max_age
111     self._store_on_get = store_on_get
112     self._return_source_on_none = return_source_on_none
113 #
114 self._source_get_keys = []
115 self._cached_props = None
116
117 def add_source_get_keys(self, keys):
118     """
119     This will add one or more keys to a list of keys which will always be provided by the
120     ``source_instance`` instead of the cache.
121
122     :param keys: The key or keys to be added
123     :type keys: list, tuple, str
124     """
```

Unittest for caching

```

119     if type(keys) in [list, tuple]:
120         self._source_get_keys.extend(keys)
121     else:
122         self._source_get_keys.append(keys)
123
124     def full_update(self, sleep_between_keys=0):
125         """
126         With the execution of this method, the complete source data which needs to be cached,
127         will be read from the source instance
128         and the resulting cache will be stored to the given file.
129
130         :param sleep_between_keys: Time to sleep between each source data generation
131         :type sleep_between_keys: float, int
132
133         .. hint:: Use this method, if you initialised the class with `store_on_get=False`
134         """
135         self._load_source(sleep_between_keys=sleep_between_keys)
136         self._save_cache()
137
138     def get(self, key, default=None):
139         """
140         Method to get the cached property. If the key does not exists in the cache or `
141         source_instance`, `default` will be returned.
142
143         :param key: key for value to get.
144         :param default: value to be returned, if key does not exists.
145         :returns: value for a given key or default value.
146         """
147         # Init cache
148         if self._cached_props is None:
149             self._init_cache()
150         # Identify old cache
151         if self._max_age is None:
152             cache_old = False
153         else:
154             cache_old = time.time() - self._cached_props[self.AGE_TAG].get(self._key_filter(key),
155             0) > self._max_age
156         if cache_old:
157             logger.debug("The cached value is old, cached value will be ignored")
158         # Return cached value
159         if not cache_old and key not in self._source_get_keys and self._key_filter(key) in self.
160         _cached_props[self.DATA_TAG]:
161             logger.debug("Providing property for '%s' from cache", key)
162             rv = self._cached_props[self.DATA_TAG].get(self._key_filter(key), default)
163             if rv is not None or not self._return_source_on_none:
164                 return rv
165         # Create cache and return value
166         if key in self._source_instance.keys():
167             logger.debug("Loading property for key='%s' from source instance", key)
168             val = self._source_instance.get(key, None)
169             if self._store_on_get:
170                 tm = int(time.time())
171                 logger.debug("Adding key=%s, value=%s with timestamp=%d to chache", key, val, tm)
172                 self._cached_props[self.DATA_TAG][self._key_filter(key)] = val
173                 self._cached_props[self.AGE_TAG][self._key_filter(key)] = tm
174                 self._save_cache()
175             else:
176                 return val
177         cached_data = self._cached_props[self.DATA_TAG].get(self._key_filter(key), default)
178         if cached_data is None and self._return_source_on_none:
179             return self._source_instance.get(key, default)
180         return cached_data

```

Unittest for caching

```
177         else:
178             if key not in self._source_instance.keys():
179                 logger.debug("Key '%s' is not in cached.keys. Uncached data will be returned.",
key)
180             else:
181                 logger.debug("Key '%s' is excluded by .add_source_get_keys(). Uncached data will
be returned.", key)
182             return self._source_instance.get(key, default)
183
184     def _data_version(self):
185         if self._cached_props is None:
186             return None
187         else:
188             return self._cached_props.get(self.DATA_VERSION_TAG, None)
189
190     def _storage_version(self):
191         if self._cached_props is None:
192             return None
193         else:
194             return self._cached_props.get(self.STORAGE_VERSION_TAG, None)
195
196     def _init_cache(self):
197         load_cache = self._load_cache()
198         uid = self._source_instance.uid() != self._uid()
199         try:
200             data_version = self._source_instance.data_version() > self._data_version()
201         except TypeError:
202             data_version = True
203         try:
204             storage_version = self._storage_version() != self.STORAGE_VERSION
205         except TypeError:
206             storage_version = True
207         #
208         if not load_cache or uid or data_version or storage_version:
209             if load_cache:
210                 if self._uid() is not None and uid:
211                     logger.debug("Source uid changed, ignoring previous cache data")
212                 if self._data_version() is not None and data_version:
213                     logger.debug("Data version increased, ignoring previous cache data")
214                 if storage_version:
215                     logger.debug("Storage version changed, ignoring previous cache data")
216             self._cached_props = {self.AGE_TAG: {}, self.DATA_TAG: {}}
217             if self._load_all_on_init:
218                 self._load_source()
219             self._cached_props[self.UID_TAG] = self._source_instance.uid()
220             self._cached_props[self.DATA_VERSION_TAG] = self._source_instance.data_version()
221             self._cached_props[self.STORAGE_VERSION_TAG] = self.STORAGE_VERSION
222
223     def _load_only(self):
224         with open(self._cache_filename, 'rb') as fh:
225             self._cached_props = pickle.load(fh)
226         logger.debug('Loading properties from cache (%s)', self._cache_filename)
227
228     def _load_cache(self):
229         if os.path.exists(self._cache_filename):
230             try:
231                 self._load_only()
232             except:
233                 logger.exception("Exception while loading cache file %s", self._cache_filename)
234             else:
235                 return True
236         else:
```

Unittest for caching

```
237         logger.debug('Cache file does not exists (yet).')
238         return False
239
240     def _key_filter(self, key):
241         return key
242
243     def _load_source(self, sleep_between_keys=0):
244         if self._cached_props is None:
245             self._init_cache()
246         logger.debug('Loading all data from source - %s', repr(self._source_instance.keys()))
247         for key in self._source_instance.keys():
248             if key not in self._source_get_keys:
249                 self._cached_props[self.DATA_TAG][self._key_filter(key)] = self._source_instance
250                 self._cached_props[self.AGE_TAG][self._key_filter(key)] = int(time.time())
251                 time.sleep(sleep_between_keys)
252
253     def _save_only(self):
254         with open(self._cache_filename, 'wb') as fh:
255             pickle.dump(self._cached_props, fh)
256             logger.debug('cache-file stored (%s)', self._cache_filename)
257
258     def _save_cache(self):
259         self._save_only()
260         if self._callback_on_data_storage is not None:
261             self._callback_on_data_storage(self)
262
263     def _uid(self):
264         if self._cached_props is None:
265             return None
266         else:
267             return self._cached_props.get(self.UID_TAG, None)
268
269
270 class property_cache_json(property_cache_pickle):
271     """
272     See also parent :py:class:`property_cache_pickle` for detailed information.
273
274     .. important::
275         * This class uses json. You should only use keys of type string!
276         * Unicode types are transfered to strings
277
278         See limitations of json.
279
280     Example:
281
282     .. literalinclude:: caching/_examples_/property_cache_json.py
283
284     Will result on the first execution to the following output (with a long execution time):
285
286     .. literalinclude:: caching/_examples_/property_cache_json_1.log
287
288     With every following execution the time cosumption my by much smaller:
289
290     .. literalinclude:: caching/_examples_/property_cache_json_2.log
291     """
292
293     def _load_only(self):
294         with open(self._cache_filename, 'r') as fh:
295             self._cached_props = json.load(fh)
296             logger.debug('Loading properties from cache (%s)', self._cache_filename)
297
298     def _save_only(self):
299         with open(self._cache_filename, 'w') as fh:
300             json.dump(self._cached_props, fh, sort_keys=True, indent=4)
301             logger.debug('cache-file stored (%s)', self._cache_filename)
```