

Unittest for media

February 2, 2020

Contents

1	Test Information	3
1.1	Test Candidate Information	3
1.2	Unittest Information	3
1.3	Test System Information	3
2	Statistic	3
2.1	Test-Statistic for testrun with python 3.6.9 (final)	3
2.2	Coverage Statistic	4
3	Tested Requirements	5
3.1	Metadata	5
3.1.1	Method to get Metadata	5
3.2	Image	6
3.2.1	Load from File	6
3.2.2	Save	7
3.2.3	Image data	7
3.2.4	Resize	7
3.2.5	Rotate	8
3.2.6	Join	8
A	Trace for testrun with python 3.6.9 (final)	10
A.1	Tests with status Info (7)	10
A.1.1	Method to get Metadata	10
A.1.2	Load from File	13
A.1.3	Save	14
A.1.4	Image data	15
A.1.5	Resize	15
A.1.6	Rotate	16
A.1.7	Join	18

B Test-Coverage	20
B.1 media	20
B.1.1 media.__init__.py	20
B.1.2 media.common.py	24
B.1.3 media.convert.py	25
B.1.4 media.metadata.py	25

1 Test Information

1.1 Test Candidate Information

The Module `media` is designed to help on all issues with media files, like tags (e.g. `exif`, `id3`) and transformations. For more Information read the documentation.

Library Information	
Name	media
State	Released
Supported Interpreters	python3
Version	8ad0730237b133d3d03c875bf7f97bba

Dependencies	
--------------	--

1.2 Unittest Information

Unittest Information	
Version	19140f198948fc7dd014a1ac1cd02dcf
Testruns with	python 3.6.9 (final)

1.3 Test System Information

System Information	
Architecture	64bit
Distribution	LinuxMint 19.3 tricia
Hostname	ahorn
Kernel	5.3.0-28-generic (#30 18.04.1-Ubuntu SMP Fri Jan 17 06:14:09 UTC 2020)
Machine	x86_64
Path	/user_data/data/dirk/prj/unittest/media/unittest
System	Linux
Username	dirk

2 Statistic

2.1 Test-Statistic for testrun with python 3.6.9 (final)

Number of tests	7
Number of successfull tests	7
Number of possibly failed tests	0
Number of failed tests	0

Executionlevel	Full Test (all defined tests)
Time consumption	14.265s

2.2 Coverage Statistic

Module- or Filename	Line-Coverage	Branch-Coverage
media	97.8%	96.7%
media.__init__.py	99.3%	
media.common.py	100.0%	
media.convert.py	86.7%	
media.metadata.py	98.1%	

3 Tested Requirements

3.1 Metadata

3.1.1 Method to get Metadata

Description

A Method shall return the metadata for a given media filename.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.1!

Testrun:	python 3.6.9 (final)
Caller:	/user_data/data/dirk/prj/unittest/media/unittest/src/tests/_init_.py (27)
Start-Time:	2020-02-02 23:50:04,982
Finished-Time:	2020-02-02 23:50:06,653
Time-Consumption	1.672s

Testsummary:

Success	Media data for unknown.txt is correct (Content None and Type is <class 'NoneType'>).
Success	Media data for audio.mp3 is correct (Content {'duration': 236.094694, 'bitrate': 290743, 'artist': 'Kaleo', 'title': 'No Good', 'album': 'A/B', 'track': 1, 'genre': 'Rock', 'year': 2016, 'size': 8580366, 'time': 1451606398, 'tm_is_subst': True} and Type is <class 'dict'>).
Success	Media data for audio_fail_conv.mp3 is correct (Content {'duration': 281.991837, 'bitrate': 228298, 'title': 'Video Games (Album Version Remastered)', 'artist': 'Lana Del Rey', 'album': 'Born To Die', 'genre': 'Pop', 'track': 4, 'year': 2012, 'size': 8047290, 'time': 1325375995, 'tm_is_subst': True} and Type is <class 'dict'>).
Success	Media data for audio_year_0.mp3 is correct (Content {'duration': 120.476735, 'bitrate': 240202, 'title': 'Was bringt der Dezember', 'artist': 'Rolf und seine Freunde', 'album': 'Wir warten auf Weihnachten', 'year': 0, 'track': 9, 'genre': 'Other', 'size': 3617354} and Type is <class 'dict'>).
Success	Media data for image_exif_gps.jpg is correct (Content {'time': 1560083621, 'exposure_program': 'Program Normal', 'exposure_time': 0.007633587786259542, 'flash': 'Off', 'aperture': 2.2, 'focal_length': 3.463, 'gps': {'lon': 11.574697, 'lat': 52.993599}, 'height': 3120, 'iso': 100, 'orientation': 6, 'width': 4160, 'size': 4524705, 'camera': 'motorola: motorola one'} and Type is <class 'dict'>).
Success	Media data for image_exif_no_gps.jpg is correct (Content {'time': 1515143529, 'exposure_program': 'Program Normal', 'exposure_time': 0.03, 'flash': 'Fired', 'aperture': 2.2, 'focal_length': 4.5, 'height': 3968, 'iso': 160, 'orientation': 0, 'width': 2976, 'size': 2837285, 'camera': 'HUAWEI: EVA-L09'} and Type is <class 'dict'>).
Success	Media data for image_non_exif.jpg is correct (Content {'size': 1139092, 'time': 1449870515, 'tm_is_subst': True} and Type is <class 'dict'>).
Success	Media data for image_extraction_failed.jpg is correct (Content {'time': 1226149915, 'exposure_program': 'Program Normal', 'exposure_time': 0.008, 'flash': 'Fill Fired', 'aperture': 7.1, 'focal_length': 170.0, 'height': 2592, 'iso': 400, 'orientation': 1, 'width': 3888, 'size': 1301272, 'camera': 'Canon: Canon EOS 40D'} and Type is <class 'dict'>).
Success	Media data for video.3gp is correct (Content {'width': 800, 'height': 480, 'ratio': 1.6666666666666667, 'duration': 3.964, 'bitrate': 2341765, 'time': 1414948303, 'size': 1160345} and Type is <class 'dict'>).

Success Media data for video.mp4 is correct (Content {'width': 1920, 'height': 1080, 'ratio': 1.7777777777777777, 'duration': 12.453, 'bitrate': 17883888, 'time': 1503125482, 'size': 27838508} and Type is <class 'dict'>).

Success Media data for video_special_time.avi is correct (Content {'width': 320, 'height': 240, 'ratio': 0.0, 'duration': 26.531264, 'bitrate': 840554, 'time': 1086778620, 'size': 2787622} and Type is <class 'dict'>).

Success Media data for video_no_date.avi is correct (Content {'width': 640, 'height': 480, 'ratio': 1.3333333333333333, 'duration': 11.016, 'bitrate': 2153411, 'size': 2965248, 'time': 1158528375, 'tm.is_subst': True} and Type is <class 'dict'>).

3.2 Image

The library `media` shall have a class `image`. This class shall be able to read from image or video files, pil image instances or from `media.image` instances itself. The class shall help by some common tasks like rotating, resizing, ...

3.2.1 Load from File

Description

The class `image` shall have a method `load_from_file`, which creates a copy of an image to the instance. Load from file can handle a filename, but also pil images and media images. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.2!

Testrun:	python 3.6.9 (final)
Caller:	/user_data/data/dirk/prj/unittest/media/unittest/src/tests/_init_.py (31)
Start-Time:	2020-02-02 23:50:06,655
Finished-Time:	2020-02-02 23:50:07,867
Time-Consumption	1.212s

Testsummary:

Success Type of image stored in instance, if no parameter is given is correct (Content <class 'NoneType'> and Type is <class 'type'>).

Success Type of image stored in instance, if a unsupported parameter is given is correct (Content <class 'NoneType'> and Type is <class 'type'>).

Success Type of image stored in instance, if an unknown file is given is correct (Content <class 'NoneType'> and Type is <class 'type'>).

Success Type of image stored in instance, if a image file is given is correct (Content <class 'PIL.Image.Image'> and Type is <class 'type'>).

Success Type of image stored in instance, if a video file is given is correct (Content <class 'PIL.Image.Image'> and Type is <class 'type'>).

3.2.2 Save

Description

The class `image` shall have a method `save`, which stores the modified image to a given filename. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.3!

Testrun:	python 3.6.9 (final)
Caller:	/user_data/data/dirk/prj/unittest/media/unittest/src/tests/_init_.py (32)
Start-Time:	2020-02-02 23:50:07,867
Finished-Time:	2020-02-02 23:50:08,703
Time-Consumption	0.836s

Testsummary:

Success	Returnvalue of failed save method is correct (Content False and Type is <class 'bool'>).
Success	Existance of saved file is correct (Content False and Type is <class 'bool'>).
Success	Returnvalue of successful save method is correct (Content True and Type is <class 'bool'>).
Success	Existance of saved file is correct (Content True and Type is <class 'bool'>).

3.2.3 Image data

Description

The class `image` shall have a method `image_data`, which returns the raw data of the modified image.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.4!

Testrun:	python 3.6.9 (final)
Caller:	/user_data/data/dirk/prj/unittest/media/unittest/src/tests/_init_.py (33)
Start-Time:	2020-02-02 23:50:08,703
Finished-Time:	2020-02-02 23:50:09,297
Time-Consumption	0.593s

Testsummary:

Success	Filecompare for image_data.jpg is correct (Content True and Type is <class 'bool'>).
----------------	--

3.2.4 Resize

Description

The class `image` shall have a method `resize`, which resizes the image. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.5!

Testrun: python 3.6.9 (final)
 Caller: /user_data/data/dirk/prj/unittest/media/unittest/src/tests/_init_.py (34)
 Start-Time: 2020-02-02 23:50:09,317
 Finished-Time: 2020-02-02 23:50:09,700
 Time-Consumption 0.384s

Testsummary:

Success Returnvalue of successful resize method is correct (Content True and Type is <class 'bool'>).
Success Resolution of resized image is correct (Content 300 and Type is <class 'int'>).
Success Returnvalue of failed resize method is correct (Content False and Type is <class 'bool'>).

3.2.5 Rotate

Description

The class `image` shall have a method `rotate_by_orientation`, which rotates the image by an exif orientation. If no parameter is given, the orientation will be taken out of the loaded image. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.6!

Testrun: python 3.6.9 (final)
 Caller: /user_data/data/dirk/prj/unittest/media/unittest/src/tests/_init_.py (35)
 Start-Time: 2020-02-02 23:50:09,701
 Finished-Time: 2020-02-02 23:50:13,100
 Time-Consumption 3.400s

Testsummary:

Success Returnvalue of rotate method without loading an image is correct (Content False and Type is <class 'bool'>).
Success Returnvalue of rotate method with invalid orientation is correct (Content False and Type is <class 'bool'>).
Success Returnvalue of rotate method with no orientation in method call and exif is correct (Content False and Type is <class 'bool'>).
Success Filecompare for rotated_image_none.jpg is correct (Content True and Type is <class 'bool'>).
Success Filecompare for rotated_image_6.jpg is correct (Content True and Type is <class 'bool'>).
Success Filecompare for rotated_image_8.jpg is correct (Content True and Type is <class 'bool'>).
Success Filecompare for rotated_image_3.jpg is correct (Content True and Type is <class 'bool'>).

3.2.6 Join

Description

The class `image` shall have a method `join`, which joins an image to the loaded image. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.7!

Testrun:	python 3.6.9 (final)
Caller:	/user_data/data/dirk/prj/unittest/media/unittest/src/tests/_init_...py (36)
Start-Time:	2020-02-02 23:50:13,103
Finished-Time:	2020-02-02 23:50:19,271
Time-Consumption	6.169s

Testsummary:

Success	Returnvalue of join method without loading an image is correct (Content False and Type is <class 'bool'>).
Success	Returnvalue of join method with invalid join position is correct (Content False and Type is <class 'bool'>).
Success	Returnvalue of join method with unknown join file is correct (Content False and Type is <class 'bool'>).
Success	Filecompare for joined_image_3.jpg is correct (Content True and Type is <class 'bool'>).
Success	Filecompare for joined_image_4.jpg is correct (Content True and Type is <class 'bool'>).
Success	Filecompare for joined_image_5.jpg is correct (Content True and Type is <class 'bool'>).
Success	Filecompare for joined_image_1.jpg is correct (Content True and Type is <class 'bool'>).
Success	Filecompare for joined_image_2.jpg is correct (Content True and Type is <class 'bool'>).

A Trace for testrun with python 3.6.9 (final)

A.1 Tests with status Info (7)

A.1.1 Method to get Metadata

Description

A Method shall return the metadata for a given media filename.

Testresult

This test was passed with the state: **Success**.

Success Media data for unknown.txt is correct (Content None and Type is <class 'NoneType'>).

Filetype not known: /user_data/data/dirk/prj/unittest/media/unittest/input_data/unknown.txt

Result (Media data for unknown.txt): None (<class 'NoneType'>)

Expectation (Media data for unknown.txt): result = None (<class 'NoneType'>)

Success Media data for audio.mp3 is correct (Content {'duration': 236.094694, 'bitrate': 290743, 'artist': 'Kaleo', 'title': 'No Good', 'album': 'A/B', 'track': 1, 'genre': 'Rock', 'year': 2016, 'size': 8580366, 'time': 1451606398, 'tm_is_subst': True} and Type is <class 'dict'>).

Result (Media data for audio.mp3): { 'duration': 236.094694, 'bitrate': 290743, 'artist':
 ↳ 'Kaleo', 'title': 'No Good', 'album': 'A/B', 'track': 1, 'genre': 'Rock', 'year': 2016,
 ↳ 'size': 8580366, 'time': 1451606398, 'tm_is_subst': True } (<class 'dict'>)

Expectation (Media data for audio.mp3): result = { 'duration': 236.094694, 'bitrate': 290743,
 ↳ 'artist': 'Kaleo', 'title': 'No Good', 'album': 'A/B', 'track': 1, 'genre': 'Rock',
 ↳ 'year': 2016, 'time': 1451606398, 'tm_is_subst': True, 'size': 8580366 } (<class 'dict'>)

Success Media data for audio_fail_conv.mp3 is correct (Content {'duration': 281.991837, 'bitrate': 228298, 'title': 'Video Games (Album Version Remastered)', 'artist': 'Lana Del Rey', 'album': 'Born To Die', 'genre': 'Pop', 'track': 4, 'year': 2012, 'size': 8047290, 'time': 1325375995, 'tm_is_subst': True} and Type is <class 'dict'>).

Result (Media data for audio_fail_conv.mp3): { 'duration': 281.991837, 'bitrate': 228298,
 ↳ 'title': 'Video Games (Album Version Remastered)', 'artist': 'Lana Del Rey', 'album':
 ↳ 'Born To Die', 'genre': 'Pop', 'track': 4, 'year': 2012, 'size': 8047290, 'time':
 ↳ 1325375995, 'tm_is_subst': True } (<class 'dict'>)

Expectation (Media data for audio_fail_conv.mp3): result = { 'duration': 281.991837,
 ↳ 'bitrate': 228298, 'artist': 'Lana Del Rey', 'title': 'Video Games (Album Version
 ↳ Remastered)', 'album': 'Born To Die', 'track': 4, 'genre': 'Pop', 'year': 2012, 'time':
 ↳ 1325375995, 'tm_is_subst': True, 'size': 8047290 } (<class 'dict'>)

Success Media data for audio_year_0.mp3 is correct (Content {'duration': 120.476735, 'bitrate': 240202, 'title': 'Was bringt der Dezember', 'artist': 'Rolf und seine Freunde', 'album': 'Wir warten auf Weihnachten', 'year': 0, 'track': 9, 'genre': 'Other', 'size': 3617354} and Type is <class 'dict'>).

```
Result (Media data for audio_year_0.mp3): { 'duration': 120.476735, 'bitrate': 240202,
↳ 'title': 'Was bringt der Dezember', 'artist': 'Rolf und seine Freunde', 'album': 'Wir
↳ warten auf Weihnachten', 'year': 0, 'track': 9, 'genre': 'Other', 'size': 3617354 }
↳ (<class 'dict'>)
```

```
Expectation (Media data for audio_year_0.mp3): result = { 'duration': 120.476735, 'bitrate':
↳ 240202, 'artist': 'Rolf und seine Freunde', 'title': 'Was bringt der Dezember', 'album':
↳ 'Wir warten auf Weihnachten', 'track': 9, 'genre': 'Other', 'year': 0, 'size': 3617354 }
↳ (<class 'dict'>)
```

Success Media data for image_exif_gps.jpg is correct (Content {'time': 1560083621, 'exposure_program': 'Program Normal', 'exposure_time': 0.007633587786259542, 'flash': 'Off', 'aperture': 2.2, 'focal_length': 3.463, 'gps': {'lon': 11.574697, 'lat': 52.993599}, 'height': 3120, 'iso': 100, 'orientation': 6, 'width': 4160, 'size': 4524705, 'camera': 'motorola: motorola one'} and Type is <class 'dict'>).

```
Result (Media data for image_exif_gps.jpg): { 'time': 1560083621, 'exposure_program':
↳ 'Program Normal', 'exposure_time': 0.007633587786259542, 'flash': 'Off', 'aperture': 2.2,
↳ 'focal_length': 3.463, 'gps': { 'lon': 11.574697, 'lat': 52.993599 }, 'height': 3120,
↳ 'iso': 100, 'orientation': 6, 'width': 4160, 'size': 4524705, 'camera': 'motorola:
↳ motorola one' } (<class 'dict'>)
```

```
Expectation (Media data for image_exif_gps.jpg): result = { 'time': 1560083621,
↳ 'exposure_program': 'Program Normal', 'exposure_time': 0.007633587786259542, 'flash':
↳ 'Off', 'aperture': 2.2, 'focal_length': 3.463, 'gps': { 'lon': 11.574697, 'lat':
↳ 52.993599 }, 'height': 3120, 'iso': 100, 'orientation': 6, 'width': 4160, 'camera':
↳ 'motorola: motorola one', 'size': 4524705 } (<class 'dict'>)
```

Success Media data for image_exif_no_gps.jpg is correct (Content {'time': 1515143529, 'exposure_program': 'Program Normal', 'exposure_time': 0.03, 'flash': 'Fired', 'aperture': 2.2, 'focal_length': 4.5, 'height': 3968, 'iso': 160, 'orientation': 0, 'width': 2976, 'size': 2837285, 'camera': 'HUAWEI: EVA-L09'} and Type is <class 'dict'>).

```
Result (Media data for image_exif_no_gps.jpg): { 'time': 1515143529, 'exposure_program':
↳ 'Program Normal', 'exposure_time': 0.03, 'flash': 'Fired', 'aperture': 2.2,
↳ 'focal_length': 4.5, 'height': 3968, 'iso': 160, 'orientation': 0, 'width': 2976, 'size':
↳ 2837285, 'camera': 'HUAWEI: EVA-L09' } (<class 'dict'>)
```

```
Expectation (Media data for image_exif_no_gps.jpg): result = { 'time': 1515143529,
↳ 'exposure_program': 'Program Normal', 'exposure_time': 0.03, 'flash': 'Fired',
↳ 'aperture': 2.2, 'focal_length': 4.5, 'height': 3968, 'iso': 160, 'orientation': 0,
↳ 'width': 2976, 'camera': 'HUAWEI: EVA-L09', 'size': 2837285 } (<class 'dict'>)
```

Success Media data for image_non_exif.jpg is correct (Content {'size': 1139092, 'time': 1449870515, 'tm.is.subst': True} and Type is <class 'dict'>).

```
/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_non_exif.jpg does not have
↳ any exif information
```

```
Result (Media data for image_non_exif.jpg): { 'size': 1139092, 'time': 1449870515,
↳ 'tm_is_subst': True } (<class 'dict'>)
```

```
Expectation (Media data for image_non_exif.jpg): result = { 'time': 1449870515,
↳ 'tm_is_subst': True, 'size': 1139092 } (<class 'dict'>)
```

Success Media data for image_extraction_failed.jpg is correct (Content {'time': 1226149915, 'exposure_program': 'Program Normal', 'exposure_time': 0.008, 'flash': 'Fill Fired', 'aperture': 7.1, 'focal_length': 170.0, 'height': 2592, 'iso': 400, 'orientation': 1, 'width': 3888, 'size': 1301272, 'camera': 'Canon: Canon EOS 40D'} and Type is <class 'dict'>).

GPS data extraction failed for {0: b'\x02\x02\x00\x00'}

```
Result (Media data for image_extraction_failed.jpg): { 'time': 1226149915,
↳ 'exposure_program': 'Program Normal', 'exposure_time': 0.008, 'flash': 'Fill Fired',
↳ 'aperture': 7.1, 'focal_length': 170.0, 'height': 2592, 'iso': 400, 'orientation': 1,
↳ 'width': 3888, 'size': 1301272, 'camera': 'Canon: Canon EOS 40D' } (<class 'dict'>)
```

```
Expectation (Media data for image_extraction_failed.jpg): result = { 'time': 1226149915,
↳ 'exposure_program': 'Program Normal', 'exposure_time': 0.008, 'flash': 'Fill Fired',
↳ 'aperture': 7.1, 'focal_length': 170.0, 'height': 2592, 'iso': 400, 'orientation': 1,
↳ 'width': 3888, 'camera': 'Canon: Canon EOS 40D', 'size': 1301272 } (<class 'dict'>)
```

Success Media data for video.3gp is correct (Content {'width': 800, 'height': 480, 'ratio': 1.6666666666666667, 'duration': 3.964, 'bitrate': 2341765, 'time': 1414948303, 'size': 1160345} and Type is <class 'dict'>).

```
Result (Media data for video.3gp): { 'width': 800, 'height': 480, 'ratio':
↳ 1.6666666666666667, 'duration': 3.964, 'bitrate': 2341765, 'time': 1414948303, 'size':
↳ 1160345 } (<class 'dict'>)
```

```
Expectation (Media data for video.3gp): result = { 'width': 800, 'height': 480, 'ratio':
↳ 1.6666666666666667, 'duration': 3.964, 'bitrate': 2341765, 'time': 1414948303, 'size':
↳ 1160345 } (<class 'dict'>)
```

Success Media data for video.mp4 is correct (Content {'width': 1920, 'height': 1080, 'ratio': 1.7777777777777777, 'duration': 12.453, 'bitrate': 17883888, 'time': 1503125482, 'size': 27838508} and Type is <class 'dict'>).

```
Result (Media data for video.mp4): { 'width': 1920, 'height': 1080, 'ratio':
↳ 1.7777777777777777, 'duration': 12.453, 'bitrate': 17883888, 'time': 1503125482, 'size':
↳ 27838508 } (<class 'dict'>)
```

```
Expectation (Media data for video.mp4): result = { 'width': 1920, 'height': 1080, 'ratio':
↳ 1.7777777777777777, 'duration': 12.453, 'bitrate': 17883888, 'time': 1503125482, 'size':
↳ 27838508 } (<class 'dict'>)
```

Success Media data for video_special_time.avi is correct (Content {'width': 320, 'height': 240, 'ratio': 0.0, 'duration': 26.531264, 'bitrate': 840554, 'time': 1086778620, 'size': 2787622} and Type is <class 'dict'>).

Can't convert 'N/A' (duration) for duration

```
Result (Media data for video_special_time.avi): { 'width': 320, 'height': 240, 'ratio': 0.0,
↳ 'duration': 26.531264, 'bitrate': 840554, 'time': 1086778620, 'size': 2787622 } (<class
↳ 'dict'>)
```

```
Expectation (Media data for video_special_time.avi): result = { 'width': 320, 'height': 240,
↳ 'ratio': 0.0, 'duration': 26.531264, 'bitrate': 840554, 'time': 1086778620, 'size':
↳ 2787622 } (<class 'dict'>)
```

Success Media data for video_no_date.avi is correct (Content {'width': 640, 'height': 480, 'ratio': 1.3333333333333333, 'duration': 11.016, 'bitrate': 2153411, 'size': 2965248, 'time': 1158528375, 'tm_is_subst': True} and Type is <class 'dict'>).

```
Result (Media data for video_no_date.avi): { 'width': 640, 'height': 480, 'ratio':
↳ 1.3333333333333333, 'duration': 11.016, 'bitrate': 2153411, 'size': 2965248, 'time':
↳ 1158528375, 'tm_is_subst': True } (<class 'dict'>)
```

```
Expectation (Media data for video_no_date.avi): result = { 'width': 640, 'height': 480,
↳ 'ratio': 1.3333333333333333, 'duration': 11.016, 'bitrate': 2153411, 'time': 1158528375,
↳ 'tm_is_subst': True, 'size': 2965248 } (<class 'dict'>)
```

A.1.2 Load from File

Description

The class `image` shall have a method `load_from_file`, which creates a copy of an image to the instance. Load from file can handle a filename, but also pil images and media images. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**.

Success Type of image stored in instance, if no parameter is given is correct (Content <class 'NoneType'> and Type is <class 'type'>).

```
Result (Type of image stored in instance, if no parameter is given): <class 'NoneType'>
↳ (<class 'type'>)
```

```
Expectation (Type of image stored in instance, if no parameter is given): result = <class
↳ 'NoneType'> (<class 'type'>)
```

Success Type of image stored in instance, if a unsupported parameter is given is correct (Content <class 'NoneType'> and Type is <class 'type'>).

Instance type is not supported: <class 'int'>

```
Result (Type of image stored in instance, if a unsupported parameter is given): <class
↳ 'NoneType'> (<class 'type'>)
```

```
Expectation (Type of image stored in instance, if a unsupported parameter is given): result =
↳ <class 'NoneType'> (<class 'type'>)
```

Success Type of image stored in instance, if an unknown file is given is correct (Content <class 'NoneType'> and Type is <class 'type'>).

Filetype is not supported

↪ (/user_data/data/dirk/prj/unittest/media/unittest/input_data/unknown.txt)

Result (Type of image stored in instance, if an unknown file is given): <class 'NoneType'>

↪ (<class 'type'>)

Expectation (Type of image stored in instance, if an unknown file is given): result = <class

↪ 'NoneType'> (<class 'type'>)

Success Type of image stored in instance, if a image file is given is correct (Content <class 'PIL.Image.Image'> and Type is <class 'type'>).

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'

Result (Type of image stored in instance, if a image file is given): <class

↪ 'PIL.Image.Image'> (<class 'type'>)

Expectation (Type of image stored in instance, if a image file is given): result = <class

↪ 'PIL.Image.Image'> (<class 'type'>)

Success Type of image stored in instance, if a video file is given is correct (Content <class 'PIL.Image.Image'> and Type is <class 'type'>).

loading image from '/user_data/data/dirk/prj/unittest/media/unittest/input_data/video.mp4'

Result (Type of image stored in instance, if a video file is given): <class

↪ 'PIL.Image.Image'> (<class 'type'>)

Expectation (Type of image stored in instance, if a video file is given): result = <class

↪ 'PIL.Image.Image'> (<class 'type'>)

A.1.3 Save

Description

The class image shall have a method save, which stores the modified image to a given filename. The method returns True on success and False on failures.

Testresult

This test was passed with the state: **Success**.

Success Returnvalue of failed save method is correct (Content False and Type is <class 'bool'>).

No image available to be saved

↪ ('/user_data/data/dirk/prj/unittest/media/unittest/output_data/saved_image.jpg')

Result (Returnvalue of failed save method): False (<class 'bool'>)

Expectation (Returnvalue of failed save method): result = False (<class 'bool'>)

Success Existence of saved file is correct (Content False and Type is <class 'bool'>).

```
Result (Existance of saved file): False (<class 'bool'>)
```

```
Expectation (Existance of saved file): result = False (<class 'bool'>)
```

Success Returnvalue of successful save method is correct (Content True and Type is <class 'bool'>).

```
loading image from '/user_data/data/dirk/prj/unittest/media/unittest/input_data/video.mp4'
```

```
Saving image to '/user_data/data/dirk/prj/unittest/media/unittest/output_data/saved_image.jpg'
```

```
Result (Returnvalue of successful save method): True (<class 'bool'>)
```

```
Expectation (Returnvalue of successful save method): result = True (<class 'bool'>)
```

Success Existance of saved file is correct (Content True and Type is <class 'bool'>).

```
Result (Existance of saved file): True (<class 'bool'>)
```

```
Expectation (Existance of saved file): result = True (<class 'bool'>)
```

A.1.4 Image data

Description

The class `image` shall have a method `image_data`, which returns the raw data of the modified image.

Testresult

This test was passed with the state: **Success**.

Success Filecompare for image_data.jpg is correct (Content True and Type is <class 'bool'>).

```
loading image from
```

```
↳ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_no_gps.jpg'
```

```
Result (Filecompare for image_data.jpg): True (<class 'bool'>)
```

```
Expectation (Filecompare for image_data.jpg): result = True (<class 'bool'>)
```

A.1.5 Resize

Description

The class `image` shall have a method `resize`, which resizes the image. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**.

Success Returnvalue of successful resize method is correct (Content True and Type is <class 'bool'>).

```
loading image from
↳ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'
Resizing picture to max 300 pixel in whatever direction
Result (Returnvalue of successful resize method): True (<class 'bool'>)
Expectation (Returnvalue of successful resize method): result = True (<class 'bool'>)
```

Success Resolution of resized image is correct (Content 300 and Type is <class 'int'>).

```
Saving image to
↳ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/resized_image.jpg'
Result (Resolution of resized image): 300 (<class 'int'>)
Expectation (Resolution of resized image): result = 300 (<class 'int'>)
```

Success Returnvalue of failed resize method is correct (Content False and Type is <class 'bool'>).

```
No image available to be resized
Result (Returnvalue of failed resize method): False (<class 'bool'>)
Expectation (Returnvalue of failed resize method): result = False (<class 'bool'>)
```

A.1.6 Rotate

Description

The class `image` shall have a method `rotate_by_orientation`, which rotates the image by an exif orientation. If no parameter is given, the orientation will be taken out of the loaded image. The method returns `True` on success and `False` on failures.

Testresult

This test was passed with the state: **Success**.

Success Returnvalue of rotate method without loading an image is correct (Content False and Type is <class 'bool'>).

```
No image available, rotation not possible
Result (Returnvalue of rotate method without loading an image): False (<class 'bool'>)
Expectation (Returnvalue of rotate method without loading an image): result = False (<class 'bool'>)
↳ 'bool'>)
```

Success Returnvalue of rotate method with invalid orientation is correct (Content False and Type is <class 'bool'>).

```
loading image from
↳ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'
Orientation 17 unknown for rotation
Result (Returnvalue of rotate method with invalid orientation): False (<class 'bool'>)
Expectation (Returnvalue of rotate method with invalid orientation): result = False (<class 'bool'>)
↳ 'bool'>)
```

Success Returnvalue of rotate method with no orientation in method call and exif is correct (Content False and Type is <class 'bool'>).

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_non_exif.jpg'

Result (Returnvalue of rotate method with no orientation in method call and exif): False

↪ (<class 'bool'>)

Expectation (Returnvalue of rotate method with no orientation in method call and exif):

↪ result = False (<class 'bool'>)

Success Filecompare for rotated_image_none.jpg is correct (Content True and Type is <class 'bool'>).

Rotate with orientation None

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'

No orientation given, orientation 6 extract from exif data

Rotating picture by 270

Saving image to

↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/rotated_image_none.jpg'

Result (Filecompare for rotated_image_none.jpg): True (<class 'bool'>)

Expectation (Filecompare for rotated_image_none.jpg): result = True (<class 'bool'>)

Success Filecompare for rotated_image_6.jpg is correct (Content True and Type is <class 'bool'>).

Rotate with orientation 6

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'

Rotating picture by 270

Saving image to

↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/rotated_image_6.jpg'

Result (Filecompare for rotated_image_6.jpg): True (<class 'bool'>)

Expectation (Filecompare for rotated_image_6.jpg): result = True (<class 'bool'>)

Success Filecompare for rotated_image_8.jpg is correct (Content True and Type is <class 'bool'>).

Rotate with orientation 8

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'

Rotating picture by 90

Saving image to

↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/rotated_image_8.jpg'

Result (Filecompare for rotated_image_8.jpg): True (<class 'bool'>)

Expectation (Filecompare for rotated_image_8.jpg): result = True (<class 'bool'>)

Success Filecompare for rotated_image_3.jpg is correct (Content True and Type is <class 'bool'>).

```

Rotate with orientation 3
loading image from
↳ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'
Rotating picture by 180
Saving image to
↳ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/rotated_image_3.jpg'
Result (Filecompare for rotated_image_3.jpg): True (<class 'bool'>)
Expectation (Filecompare for rotated_image_3.jpg): result = True (<class 'bool'>)
    
```

A.1.7 Join

Description

The class image shall have a method join, which joins an image to the loaded image. The method returns True on success and False on failures.

Testresult

This test was passed with the state: **Success**.

Success Returnvalue of join method without loading an image is correct (Content False and Type is <class 'bool'>).

No image available, joining not possible

```

Result (Returnvalue of join method without loading an image): False (<class 'bool'>)
Expectation (Returnvalue of join method without loading an image): result = False (<class
↳ 'bool'>)
    
```

Success Returnvalue of join method with invalid join position is correct (Content False and Type is <class 'bool'>).

```

loading image from
↳ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'
    
```

Join position value 17 is not supported

```

Result (Returnvalue of join method with invalid join position): False (<class 'bool'>)
Expectation (Returnvalue of join method with invalid join position): result = False (<class
↳ 'bool'>)
    
```

Success Returnvalue of join method with unknown join file is correct (Content False and Type is <class 'bool'>).

```

loading image from
↳ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'
    
```

Instance type is not supported: <class 'int'>

Image to be joined is not supported None

```

Result (Returnvalue of join method with unknown join file): False (<class 'bool'>)
Expectation (Returnvalue of join method with unknown join file): result = False (<class
↳ 'bool'>)
    
```

Success Filecompare for joined_image_3.jpg is correct (Content True and Type is <class 'bool'>).

Join with position 3

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_no_gps.jpg'

Resizing picture to max 300 pixel in whatever direction

Joining two images

Saving image to

↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/joined_image_3.jpg'

Result (Filecompare for joined_image_3.jpg): True (<class 'bool'>)

Expectation (Filecompare for joined_image_3.jpg): result = True (<class 'bool'>)

Success Filecompare for joined_image_4.jpg is correct (Content True and Type is <class 'bool'>).

Join with position 4

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_no_gps.jpg'

Resizing picture to max 300 pixel in whatever direction

Joining two images

Saving image to

↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/joined_image_4.jpg'

Result (Filecompare for joined_image_4.jpg): True (<class 'bool'>)

Expectation (Filecompare for joined_image_4.jpg): result = True (<class 'bool'>)

Success Filecompare for joined_image_5.jpg is correct (Content True and Type is <class 'bool'>).

Join with position 5

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'

loading image from

↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_no_gps.jpg'

Resizing picture to max 300 pixel in whatever direction

Joining two images

Saving image to

↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/joined_image_5.jpg'

Result (Filecompare for joined_image_5.jpg): True (<class 'bool'>)

Expectation (Filecompare for joined_image_5.jpg): result = True (<class 'bool'>)

Success Filecompare for joined_image_1.jpg is correct (Content True and Type is <class 'bool'>).

```

Join with position 1
loading image from
↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'
loading image from
↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_no_gps.jpg'
Resizing picture to max 300 pixel in whatever direction
Joining two images
Saving image to
↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/joined_image_1.jpg'
Result (Filecompare for joined_image_1.jpg): True (<class 'bool'>)
Expectation (Filecompare for joined_image_1.jpg): result = True (<class 'bool'>)

```

Success Filecompare for joined_image_2.jpg is correct (Content True and Type is <class 'bool'>).

```

Join with position 2
loading image from
↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_gps.jpg'
loading image from
↪ '/user_data/data/dirk/prj/unittest/media/unittest/input_data/image_exif_no_gps.jpg'
Resizing picture to max 300 pixel in whatever direction
Joining two images
Saving image to
↪ '/user_data/data/dirk/prj/unittest/media/unittest/output_data/joined_image_2.jpg'
Result (Filecompare for joined_image_2.jpg): True (<class 'bool'>)
Expectation (Filecompare for joined_image_2.jpg): result = True (<class 'bool'>)

```

B Test-Coverage

B.1 media

The line coverage for media was 97.8%

The branch coverage for media was 96.7%

B.1.1 media.__init__.py

The line coverage for media.__init__.py was 99.3%

The branch coverage for media.__init__.py was 96.7%

```

1 #!/usr/bin/env python
2 # -*- coding: utf-8 -*-
3 #
4 """

```

```

5 media (Media Tools)
6 =====
7
8 **Author:**
9
10 * Dirk Alders <sudo-dirk@mount-mockery.de>
11
12 **Description:**
13
14     This module helps on all issues with media files , like tags (e.g. exif, id3) and
15     transformations.
16
17 **Submodules:**
18
19 * :func:`media.get_media_data`
20 * :class:`media.image`
21
22 **Unittest:**
23
24     See also the :download:`unittest <../../media/_testresults_/unittest.pdf>` documentation.
25 """
26
27 __DEPENDENCIES__ = []
28
29 import io
30 import logging
31 from PIL import Image, ImageEnhance, ExifTags
32
33 logger_name = 'MEDIA'
34 logger = logging.getLogger(logger_name)
35
36 __DESCRIPTION__ = """The Module {\\tt %s} is designed to help on all issues with media files ,
37     like tags (e.g. exif, id3) and transformations.
38 For more Information read the documentation.""" % __name__.replace('-', '\\-')
39 """The Module Description"""
40 __INTERPRETER__ = (3, )
41 """The Tested Interpreter-Versions"""
42
43
44 KEY_ALBUM = 'album'
45 KEY_APERTURE = 'aperture'
46 KEY_ARTIST = 'artist'
47 KEY_BITRATE = 'bitrate'
48 KEY_CAMERA = 'camera'
49 KEY_DURATION = 'duration'
50 KEY_EXPOSURE_PROGRAM = 'exposure_program'
51 KEY_EXPOSURE_TIME = 'exposure_time'
52 KEY_FLASH = 'flash'
53 KEY_FOCAL_LENGTH = 'focal_length'
54 KEY_GENRE = 'genre'
55 KEY_GPS = 'gps'
56 KEY_HEIGHT = 'height'
57 KEY_ISO = 'iso'
58 KEY_ORIENTATION = 'orientation'
59 KEY_RATIO = 'ratio'
60 KEY_SIZE = 'size'
61 KEY_TIME = 'time' # USE time.localtime(value) or datetime.fromtimestamp(value) to convert the
62     timestamp
63 KEY_TIME.IS.SUBSTITUTION = 'tm_is_subst'
64 KEY_TITLE = 'title'
65 KEY_TRACK = 'track'
66 KEY_WIDTH = 'width'
67 KEY_YEAR = 'year'

```

Unittest for media

```
65
66
67 def get_media_data(full_path):
68     from media.metadata import get_audio_data, get_image_data, get_video_data
69     from media.common import get_filetype, FILETYPE_AUDIO, FILETYPE_IMAGE, FILETYPE_VIDEO
70     #
71     ft = get_filetype(full_path)
72     #
73     if ft == FILETYPE_AUDIO:
74         return get_audio_data(full_path)
75     elif ft == FILETYPE_IMAGE:
76         return get_image_data(full_path)
77     elif ft == FILETYPE_VIDEO:
78         return get_video_data(full_path)
79     else:
80         logger.warning('Filetype not known: %s', full_path)
81
82
83 ORIENTATION_NORMAL = 1
84 ORIENTATION_VERTICAL_MIRRORED = 2
85 ORIENTATION_HALF_ROTATED = 3
86 ORIENTATION_HORIZONTAL_MIRRORED = 4
87 ORIENTATION_LEFT_ROTATED = 6
88 ORIENTATION_RIGHT_ROTATED = 8
89
90 JOIN_TOP_LEFT = 1
91 JOIN_TOP_RIGHT = 2
92 JOIN_BOT_LEFT = 3
93 JOIN_BOT_RIGHT = 4
94 JOIN_CENTER = 5
95
96
97 class image(object):
98     def __init__(self, media_instance=None):
99         if media_instance is not None:
100             self.load_from_file(media_instance)
101         else:
102             self._im = None
103
104     def load_from_file(self, media_instance):
105         from media.convert import get_pil_image
106         #
107         self._im = get_pil_image(media_instance)
108         if self._im is None:
109             return False
110         try:
111             self._exif = dict(self._im._getexif().items())
112         except AttributeError:
113             self._exif = {}
114         if type(self._im) is not Image.Image:
115             self._im = self._im.copy()
116         logger.debug('loading image from %s', repr(media_instance))
117         return True
118
119     def save(self, full_path):
120         if self._im is None:
121             logger.warning('No image available to be saved (%s)', repr(full_path))
122             return False
123         else:
124             logger.debug('Saving image to %s', repr(full_path))
125             with open(full_path, 'w') as fh:
126                 im = self._im.convert('RGB')
127                 im.save(fh, 'JPEG')
128         return True
```

```

129
130 def image_data(self):
131     im = self._im.copy().convert('RGB')
132     output = io.BytesIO()
133     im.save(output, format='JPEG')
134     return output.getvalue()
135
136 def resize(self, max_size):
137     if self._im is None:
138         logger.warning('No image available to be resized')
139         return False
140     else:
141         logger.debug('Resizing picture to max %d pixel in whatever direction', max_size)
142         x, y = self._im.size
143         xy_max = max(x, y)
144         self._im = self._im.resize((int(x * float(max_size) / xy_max), int(y * float(max_size) / xy_max)), Image.NEAREST).rotate(0)
145         return True
146
147 def rotate_by_orientation(self, orientation=None):
148     if self._im is None:
149         logger.warning('No image available, rotation not possible')
150         return False
151
152     if orientation is None:
153         exif_tags = dict((v, k) for k, v in ExifTags.TAGS.items())
154         try:
155             orientation = self._exif[exif_tags['Orientation']]
156             logger.debug("No orientation given, orientation %s extract from exif data", repr(orientation))
157         except KeyError:
158             return False
159
160     if orientation == ORIENTATION_HALF_ROTATED:
161         angle = 180
162     elif orientation == ORIENTATION_LEFT_ROTATED:
163         angle = 270
164     elif orientation == ORIENTATION_RIGHT_ROTATED:
165         angle = 90
166     else:
167         logger.warning('Orientation %s unknown for rotation', repr(orientation))
168         return False
169     logger.debug('Rotating picture by %d ', angle)
170     self._im = self._im.rotate(angle, expand=True)
171     return True
172
173 def join(self, join_image, join_pos=JOIN_TOP_RIGHT, opacity=0.7):
174     from media.convert import get_pil_image
175
176     def rgba_copy(im):
177         if im.mode != 'RGBA':
178             return im.convert('RGBA')
179         else:
180             return im.copy()
181
182     if self._im is None:
183         logger.warning('No image available, joining not possible')
184         return False
185
186     # ensure type of join_image is PIL.Image

```



```

187     join_image = get_pil_image(join_image)
188     if join_image is None:
189         logger.warning('Image to be joined is not supported %s', repr(join_image))
190         return False
191
192     im2 = rgba_copy(join_image)
193     # change opacity of im2
194     alpha = im2.split()[3]
195     alpha = ImageEnhance.Brightness(alpha).enhance(opacity)
196     im2.putalpha(alpha)
197
198     self._im = rgba_copy(self._im)
199
200     # create a transparent layer
201     layer = Image.new('RGBA', self._im.size, (0, 0, 0, 0))
202     # draw im2 in layer
203     if join_pos == JOIN_TOP_LEFT:
204         layer.paste(im2, (0, 0))
205     elif join_pos == JOIN_TOP_RIGHT:
206         layer.paste(im2, ((self._im.size[0] - im2.size[0]), 0))
207     elif join_pos == JOIN_BOT_LEFT:
208         layer.paste(im2, (0, (self._im.size[1] - im2.size[1])))
209     elif join_pos == JOIN_BOT_RIGHT:
210         layer.paste(im2, ((self._im.size[0] - im2.size[0]), (self._im.size[1] - im2.size[1])))
211     )
212     elif join_pos == JOIN_CENTER:
213         layer.paste(im2, (int((self._im.size[0] - im2.size[0]) / 2), int((self._im.size[1] -
214     im2.size[1]) / 2)))
215     else:
216         logger.warning("Join position value %s is not supported", join_pos)
217         return False
218
219     logger.debug('Joining two images')
220     self._im = Image.composite(layer, self._im, layer)
221
222     return True

```

B.1.2 media.common.py

The line coverage for media.common.py was 100.0%

The branch coverage for media.common.py was 96.7%

```

1 import os
2
3 FILETYPE_AUDIO = 'audio'
4 FILETYPE_IMAGE = 'image'
5 FILETYPE_VIDEO = 'video'
6
7 EXTENTIONS_AUDIO = ['.mp3', ]
8 EXTENTIONS_IMAGE = ['.jpg', '.jpeg', '.jpe', '.png', '.tif', '.tiff', '.gif', ]
9 EXTENTIONS_VIDEO = ['.avi', '.mpg', '.mpeg', '.mpe', '.mov', '.qt', '.mp4', '.webm', '.ogv', '.
10     flv', '.3gp', ]
11
12 def get_filetype(full_path):
13     ext = os.path.splitext(full_path.lower())[1]
14     if ext in EXTENTIONS_AUDIO:
15         return FILETYPE_AUDIO
16     elif ext in EXTENTIONS_IMAGE:
17         return FILETYPE_IMAGE
18     elif ext in EXTENTIONS_VIDEO:
19         return FILETYPE_VIDEO

```

B.1.3 media.convert.py

The line coverage for media.convert.py was 86.7%

The branch coverage for media.convert.py was 96.7%

```

1 import io
2 from media import common, logger
3 from PIL import Image
4 import subprocess
5 import platform
6
7
8 def get_pil_image(media_instance):
9     try:
10         media_instance = media_instance._im
11     except AttributeError:
12         pass
13
14     #
15     if type(media_instance) == str:
16         ft = common.get_filetype(media_instance)
17         if ft == common.FILETYPE.IMAGE:
18             return Image.open(media_instance)
19         elif ft == common.FILETYPE.VIDEO:
20             if platform.system() == 'Linux':
21                 cmd = 'ffmpeg -ss 0.5 -i "' + media_instance + '" -vframes 1 -f image2pipe pipe:1
22                 2> /dev/null '
23             else:
24                 cmd = 'ffmpeg -ss 0.5 -i "' + media_instance + '" -vframes 1 -f image2pipe pipe:1
25                 2> NULL '
26             try:
27                 data = subprocess.check_output(cmd, shell=True)
28             except subprocess.CalledProcessError:
29                 logger.warning('ffmpeg seems to be not installed')
30                 return None
31             ffmpeg_handle = io.BytesIO(data)
32             im = Image.open(ffmpeg_handle)
33             return im.copy()
34             logger.warning('Filetype is not supported (%s)', media_instance)
35     elif type(media_instance) == Image.Image:
36         return media_instance.copy()
37     else:
38         logger.warning('Instance type is not supported: %s' % type(media_instance))

```

B.1.4 media.metadata.py

The line coverage for media.metadata.py was 98.1%

The branch coverage for media.metadata.py was 96.7%

```

1 import logging
2 import os
3 from PIL import Image
4 import media
5 import subprocess
6 import time
7
8
9 logger = media.logger
10
11

```

```

12 __KEY_CAMERA_VENDOR__ = 'camera_vendor'
13 __KEY_CAMERA_MODEL__ = 'camera_model'
14
15
16 def get_audio_data(full_path):
17     conv_key_dict = {}
18     conv_key_dict['album'] = (str, media.KEY_ALBUM)
19     conv_key_dict['TAG:album'] = (str, media.KEY_ALBUM)
20     conv_key_dict['TAG:artist'] = (str, media.KEY_ARTIST)
21     conv_key_dict['artist'] = (str, media.KEY_ARTIST)
22     conv_key_dict['bit_rate'] = (__int_conv__, media.KEY_BITRATE)
23     conv_key_dict['duration'] = (float, media.KEY_DURATION)
24     conv_key_dict['TAG:genre'] = (str, media.KEY_GENRE)
25     conv_key_dict['genre'] = (str, media.KEY_GENRE)
26     conv_key_dict['TAG:title'] = (str, media.KEY_TITLE)
27     conv_key_dict['title'] = (str, media.KEY_TITLE)
28     conv_key_dict['TAG:track'] = (__int_conv__, media.KEY_TRACK)
29     conv_key_dict['track'] = (__int_conv__, media.KEY_TRACK)
30     conv_key_dict['TAG:date'] = (__int_conv__, media.KEY_YEAR)
31     conv_key_dict['date'] = (__int_conv__, media.KEY_YEAR)
32     return __adapt__data__(__get_xprobe_data__(full_path, conv_key_dict), full_path)
33
34
35 def get_video_data(full_path):
36     conv_key_dict = {}
37     conv_key_dict['creation_time'] = (__vid_datetime_conv__, media.KEY_TIME)
38     conv_key_dict['TAG:creation_time'] = (__vid_datetime_conv__, media.KEY_TIME)
39     conv_key_dict['bit_rate'] = (__int_conv__, media.KEY_BITRATE)
40     conv_key_dict['duration'] = (float, media.KEY_DURATION)
41     conv_key_dict['height'] = (__int_conv__, media.KEY_HEIGHT)
42     conv_key_dict['width'] = (__int_conv__, media.KEY_WIDTH)
43     conv_key_dict['display_aspect_ratio'] = (__ratio_conv__, media.KEY_RATIO)
44     return __adapt__data__(__get_xprobe_data__(full_path, conv_key_dict), full_path)
45
46
47 def get_image_data(full_path):
48     return __adapt__data__(__get_exif_data__(full_path), full_path)
49
50
51 def __adapt__data__(data, full_path):
52     data[media.KEY_SIZE] = os.path.getsize(full_path)
53     # Join Camera Vendor and Camera Model
54     if __KEY_CAMERA_MODEL__ in data and __KEY_CAMERA_VENDOR__ in data:
55         model = data.pop(__KEY_CAMERA_MODEL__)
56         vendor = data.pop(__KEY_CAMERA_VENDOR__)
57         data[media.KEY_CAMERA] = '%s: %s' % (vendor, model)
58     # Add time if not exists
59     if media.KEY_TIME not in data:
60         if media.KEY_YEAR in data and media.KEY_TRACK in data:
61             if data[media.KEY_YEAR] != 0: # ignore year 0 - must be wrong
62                 # Use a date where track 1 is the newest in the given year
63                 minute = int(data[media.KEY_TRACK] / 60)
64                 second = (data[media.KEY_TRACK] - 60 * minute) % 60
65                 #
66                 data[media.KEY_TIME] = int(time.mktime((data[media.KEY_YEAR], 1, 1, 0, 59 -
67                 minute, 59 - second, 0, 0, 0)))
68                 data[media.KEY_TIME_IS_SUBSTITUTION] = True
69             else:
70                 data[media.KEY_TIME] = int(os.path.getmtime(full_path))
71                 data[media.KEY_TIME_IS_SUBSTITUTION] = True
72     return data

```

Unittest for media

```

72
73
74 def __get_xprobe_data__(full_path, conv_key_dict):
75     def _ffprobe_command(full_path):
76         return ['ffprobe', '-v', 'quiet', '-show_format', '-show_streams', full_path]
77
78     def _avprobe_command(full_path):
79         return ['avprobe', '-v', 'quiet', '-show_format', '-show_streams', full_path]
80
81     try:
82         xprobe_text = subprocess.check_output(_avprobe_command(full_path))
83     except FileNotFoundError:
84         try:
85             xprobe_text = subprocess.check_output(_ffprobe_command(full_path))
86         except FileNotFoundError:
87             logger.warning('ffprobe and avprobe seem to be not installed')
88             return {}
89
90     #
91     rv = {}
92     for line in xprobe_text.decode('utf-8').splitlines():
93         try:
94             key, val = [snippet.strip() for snippet in line.split('=')]
95         except ValueError:
96             continue
97         else:
98             if key in conv_key_dict:
99                 tp, name = conv_key_dict[key]
100                try:
101                    rv[name] = tp(val)
102                except ValueError:
103                    logger.log(logging.WARNING if val else logging.INFO, 'Can\'t convert %s (%s)
104                    for %s', repr(val), name, name)
105
106     return rv
107
108
109 def __get_exif_data__(full_path):
110     rv = {}
111     im = Image.open(full_path)
112     try:
113         exif = dict(im._getexif().items())
114     except AttributeError:
115         logger.debug('%s does not have any exif information', full_path)
116     else:
117         conv_key_dict = {}
118         # IMAGE
119         conv_key_dict[0x9003] = (__datetime_conv__, media.KEY_TIME)
120         conv_key_dict[0x8822] = (__exposure_program_conv__, media.KEY_EXPOSURE_PROGRAM)
121         conv_key_dict[0x829A] = (__num_denum_conv__, media.KEY_EXPOSURE_TIME)
122         conv_key_dict[0x9209] = (__flash_conv__, media.KEY_FLASH)
123         conv_key_dict[0x829D] = (__num_denum_conv__, media.KEY_APERTURE)
124         conv_key_dict[0x920A] = (__num_denum_conv__, media.KEY_FOCAL_LENGTH)
125         conv_key_dict[0x8825] = (__gps_conv__, media.KEY_GPS)
126         conv_key_dict[0xA003] = (__int_conv__, media.KEY_HEIGHT)
127         conv_key_dict[0x8827] = (__int_conv__, media.KEY_ISO)
128         conv_key_dict[0x010F] = (str, __KEY_CAMERA_VENDOR__)
129         conv_key_dict[0x0110] = (str, __KEY_CAMERA_MODEL__)
130         conv_key_dict[0x0112] = (__int_conv__, media.KEY_ORIENTATION)
131         conv_key_dict[0xA002] = (__int_conv__, media.KEY_WIDTH)
132
133     for key in conv_key_dict:
134         if key in exif:
135             tp, name = conv_key_dict[key]
136             value = tp(exif[key])
137             if value is not None:
138                 rv[name] = value
139
140     return rv

```

Unittest for media

136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199

```

# TODO: Join datetime converter __datetime_conv__ and __vid_datetime_conv__
def __datetime_conv__(dt):
    format_string = "%Y:%m:%d %H:%M:%S"
    return int(time.mktime(time.strptime(dt, format_string)))

def __vid_datetime_conv__(dt):
    try:
        dt = dt[:dt.index('.')]
    except ValueError:
        pass # time string seems to have no '.'
    dt = dt.replace('T', ' ').replace('/', ' ').replace('\\', '\\')
    if len(dt) == 16:
        dt += ':00'
    format_string = '%Y-%m-%d %H:%M:%S'
    return int(time.mktime(time.strptime(dt, format_string)))

def __exposure_program_conv__(n):
    return {
        0: 'Unidentified',
        1: 'Manual',
        2: 'Program Normal',
        3: 'Aperture Priority',
        4: 'Shutter Priority',
        5: 'Program Creative',
        6: 'Program Action',
        7: 'Portrait Mode',
        8: 'Landscape Mode'
    }.get(n, None)

def __flash_conv__(n):
    return {
        0: 'No',
        1: 'Fired',
        5: 'Fired (?)', # no return sensed
        7: 'Fired (!)', # return sensed
        9: 'Fill Fired',
        13: 'Fill Fired (?)',
        15: 'Fill Fired (!)',
        16: 'Off',
        24: 'Auto Off',
        25: 'Auto Fired',
        29: 'Auto Fired (?)',
        31: 'Auto Fired (!)',
        32: 'Not Available'
    }.get(n, None)

def __int_conv__(value):
    try:
        return int(value)
    except ValueError:
        for c in ['. ', '/', '-']:
            p = value.find(c)
            if p >= 0:
                value = value[:p]
        try:
            return int(value)
        except ValueError:
            return None

```

```
200
201
202 def __num_denum_conv__(data):
203     num, denum = data
204     return num / denum
205
206
207 def __gps_conv__(data):
208     def lat_lon_cal(lon_or_lat):
209         lon_lat = 0.
210         fac = 1.
211         for num, denum in lon_or_lat:
212             lon_lat += float(num) / float(denum) * fac
213             fac *= 1. / 60.
214         return lon_lat
215     try:
216         lon = lat_lon_cal(data[0x0004])
217         lat = lat_lon_cal(data[0x0002])
218         if lon != 0 or lat != 0: # do not use lon and lat equal 0, caused by motorola gps
219             return {'lon': lon, 'lat': lat}
220     except KeyError:
221         logger.warning('GPS data extraction failed for %s', repr(data))
222
223
224 def __ratio_conv__(ratio):
225     ratio = ratio.replace('\\', '')
226     num, denum = ratio.split(':')
227     return float(num) / float(denum)
```