

Unittest for state_machine

March 23, 2025

Contents

1	Test Information	3
1.1	Test Candidate Information	3
1.2	Unittest Information	3
1.3	Test System Information	3
2	Statistic	3
2.1	Test-Statistic for testrun with python 3.11.2 (final)	3
2.2	Coverage Statistic	4
3	Tested Requirements	5
3.1	Module Initialisation	5
3.1.1	Default State	5
3.1.2	Default Last Transition Condtion	5
3.1.3	Default Previous State	6
3.1.4	Additional Keyword Arguments	6
3.2	Transition Changes	7
3.2.1	Transitiondefinition and -flow	7
3.2.2	Transitiontiming	8
3.2.3	Transitionpriorisation	9
3.3	Module Interface	9
3.3.1	This State	9
3.3.2	This State is	10
3.3.3	This State Duration	10
3.3.4	Last Transition Condition	11
3.3.5	Last Transition Condition was	12
3.3.6	Previous State	12
3.3.7	Previous State was	13
3.3.8	Previous State Duration	13
3.4	Transition Callbacks	14
3.4.1	State change callback for a defined transition and targetstate	14
3.4.2	State change callback for a defined transition	15
3.4.3	State change callback for a defined targetstate	15
3.4.4	State change callback for all kind of state changes	17
3.4.5	Execution order of Callbacks	18

A	Trace for testrun with python 3.11.2 (final)	19
A.1	Tests with status Info (20)	19
A.1.1	REQ-0005	19
A.1.2	REQ-0006	19
A.1.3	REQ-0007	19
A.1.4	REQ-0008	20
A.1.5	REQ-0017	20
A.1.6	REQ-0018	21
A.1.7	REQ-0019	22
A.1.8	REQ-0009	23
A.1.9	REQ-0010	23
A.1.10	REQ-0011	24
A.1.11	REQ-0012	24
A.1.12	REQ-0013	24
A.1.13	REQ-0014	25
A.1.14	REQ-0015	25
A.1.15	REQ-0016	26
A.1.16	REQ-0001	26
A.1.17	REQ-0002	27
A.1.18	REQ-0003	28
A.1.19	REQ-0004	29
A.1.20	REQ-0020	31
B	Test-Coverage	32
B.1	state_machine	32
B.1.1	state_machine.__init__.py	32

1 Test Information

1.1 Test Candidate Information

This Module helps implementing state machines.

Library Information

Name	state_machine
State	Released
Supported Interpreters	python3
Version	f41932a9f577e5485b47049c17da104d

Dependencies

1.2 Unittest Information

Unittest Information

Version	e6f5e3b6cb9ae84eee10254379ddd104
Testruns with	python 3.11.2 (final)

1.3 Test System Information

System Information

Architecture	64bit
Distribution	Debian GNU/Linux 12 bookworm
Hostname	ahorn
Kernel	6.1.0-17-amd64 (#1 SMP PREEMPT_DYNAMIC Debian 6.1.69-1 (2023-12-30))
Machine	x86_64
Path	/home/dirk/my_repositories/unittest/state_machine
System	Linux
Username	dirk

2 Statistic

2.1 Test-Statistic for testrun with python 3.11.2 (final)

Number of tests	20
Number of successfull tests	20
Number of possibly failed tests	0
Number of failed tests	0

Executionlevel	Full Test (all defined tests)
Time consumption	1.668s

2.2 Coverage Statistic

Module- or Filename	Line-Coverage	Branch-Coverage
state_machine	100.0%	100.0%
state_machine.__init__.py	100.0%	

3 Tested Requirements

3.1 Module Initialisation

3.1.1 Default State

Description

The state machine shall start in the state, given while module initialisation.

Reason for the implementation

Creation of a defined state after initialisation.

Fitcriterion

State machine is in the initial state after initialisation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.1!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:28,296
Finished-Time:	2025-03-23 14:39:28,296
Time-Consumption	0.000s

Testsummary:

Info	Initialising the state machine with state_c
Success	State after initialisation is correct (Content 'state_c' and Type is <class 'str'>).

3.1.2 Default Last Transition Condition

Description

The state machine shall return the string `__init__` for last transition condition after initialisation.

Reason for the implementation

Creation of a defined state after initialisation.

Fitcriterion

The last transition condition is `__init__` after initialisation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.2!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)

Start-Time: 2025-03-23 14:39:28,296
 Finished-Time: 2025-03-23 14:39:28,297
 Time-Consumption 0.000s

Testsummary:

Info Initialising the state machine with state_c
Success Last transition condition after initialisation is correct (Content '...init...' and Type is <class 'str'>).

3.1.3 Default Previous State

Description

The state machine shall return `None` for previous state after initialisation.

Reason for the implementation

Creation of a defined state after initialisation.

Fitcriterion

The previous state is `None` after initialisation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.3!

Testrun: python 3.11.2 (final)
 Caller: /home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
 Start-Time: 2025-03-23 14:39:28,297
 Finished-Time: 2025-03-23 14:39:28,297
 Time-Consumption 0.000s

Testsummary:

Info Initialising the state machine with state_c
Success Last state after initialisation is correct (Content `None` and Type is <class 'NoneType'>).

3.1.4 Additional Keyword Arguments

Description

The state machine shall store all given keyword arguments as variables of the classes instance.

Reason for the implementation

Store further information (e.g. for calculation of the transition conditions).

Fitcriterion

At least two given keyword arguments with different types are available after initialisation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.4!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/___init___py (323)
Start-Time:	2025-03-23 14:39:28,297
Finished-Time:	2025-03-23 14:39:28,297
Time-Consumption	0.001s

Testsummary:

Info	Initialising the state machine with state_c
Success	Keyword argument kw_arg_no_1 stored in state_machine is correct (Content 1 and Type is <class 'int'>).
Success	Keyword argument kw_arg_no_2 stored in state_machine is correct (Content '2' and Type is <class 'str'>).
Success	Keyword argument kw_arg_no_3 stored in state_machine is correct (Content True and Type is <class 'bool'>).
Success	Keyword argument kw_arg_no_4 stored in state_machine is correct (Content {'1': 1, '2': 'two'} and Type is <class 'dict'>).

3.2 Transition Changes

3.2.1 Transitiondefinition and -flow

Description

The user shall be able to define multiple states and transitions for the state machine. A transition shall have a start state, a target state and a transition condition. The transition condition shall be a method, where the user is able to calculate the condition on demand.

Reason for the implementation

Definition of the transitions for a state machine.

Fitcriterion

The order of at least three state changes is correct.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.5!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/___init___py (323)
Start-Time:	2025-03-23 14:39:28,298
Finished-Time:	2025-03-23 14:39:28,298
Time-Consumption	0.001s

Testsummary:

Info	Initialising state machine with state_a
Success	Initial state after Initialisation is correct (Content 'state_a' and Type is <class 'str'>).

Info Work routine executed the 1st time to do the state change. Defined Transitions are: True→state_b (0.0s); False→state_c (0.0s)

Success State after 1st execution of work method is correct (Content 'state_b' and Type is <class 'str'>).

Info Work routine executed the 2nd time to do the state change. Defined Transitions are: False→state_a (0.0s); True→state_c (0.0s)

Success State after 2nd execution of work method is correct (Content 'state_c' and Type is <class 'str'>).

Info Work routine executed the 3rd time with no effect. No Transitions starting from state_c (dead end)

Success State after 3rd execution of work method is correct (Content 'state_c' and Type is <class 'str'>).

3.2.2 Transitiontiming

Description

The user shall be able to define for each transition a transition time. On change of the transition condition to True, the transition timer starts counting the time from 0.0s. After reaching the transition time, the transition gets active.

Reason for the implementation

Robustness of the state changes (e.g. Oscillating conditions shall be ignored).

Fitcriterion

The transition time and the restart of the transition timer by setting the transition condition to False and to True again results in the expected transition timing ($\pm 0.05s$).

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.6!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/__init__.py (323)
Start-Time:	2025-03-23 14:39:28,298
Finished-Time:	2025-03-23 14:39:28,675
Time-Consumption	0.377s

Testsummary:

Info Initialising state machine with state_a

Success Initial state after Initialisation is correct (Content 'state_a' and Type is <class 'str'>).

Info Waiting for 0.160s or state change

Success State after 1st cycle is correct (Content 'state_b' and Type is <class 'str'>).

Success Transition time after 1st cycle is correct (Content 0.15043091773986816 in [0.145 ... 0.155] and Type is <class 'float'>).

Info Waiting for 0.235s or state change

Success State after 2nd cycle is correct (Content 'state_c' and Type is <class 'str'>).

Success Transition time after 2nd cycle is correct (Content 0.1502208709716797 in [0.145 ... 0.155] and Type is <class 'float'>).

Success Previous state duration is correct (Content 0.22549748420715332 in [0.21999999999999997 ... 0.22999999999999998] and Type is <class 'float'>).

3.2.3 Transitionpriorisation

Description

The state machine shall use the first active transition. If multiple transition are active, the transition with the highest overlap time will be used.

Reason for the implementation

Compensate the weakness of the execution quantisation.

Fitcriterion

At least one transition with at least two active conditions results in the expected state change.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.7!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/__init__.py (323)
Start-Time:	2025-03-23 14:39:28,676
Finished-Time:	2025-03-23 14:39:28,920
Time-Consumption	0.244s

Testsummary:

Info	Initialising state machine with state_a, a transition to state_b after 0.151s and a transition to state_c after 0.150s
Success	Initial state after Initialisation is correct (Content 'state_a' and Type is <class 'str'>).
Info	Waiting for 0.300s or state change
Success	State after 1st cycle is correct (Content 'state_c' and Type is <class 'str'>).

3.3 Module Interface

3.3.1 This State

Description

The Module shall have a method for getting the current state.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least one returned state fits to the expectation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.8!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/__init__.py (323)
Start-Time:	2025-03-23 14:39:28,921
Finished-Time:	2025-03-23 14:39:28,922
Time-Consumption	0.001s

Testsummary:

Info	Initialising the state machine with state_c
Success	Returnvalue of this_state() is correct (Content 'state.c' and Type is <class 'str'>).

3.3.2 This State is

Description

The Module shall have a method for checking if the given state is currently active.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least two calls with different return values fit to the expectation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.9!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/__init__.py (323)
Start-Time:	2025-03-23 14:39:28,922
Finished-Time:	2025-03-23 14:39:28,924
Time-Consumption	0.002s

Testsummary:

Info	Initialising the state machine with state_c
Success	Returnvalue of this_state_is(state.c) is correct (Content True and Type is <class 'bool'>).
Success	Returnvalue of this_state_is(state.b) is correct (Content False and Type is <class 'bool'>).

3.3.3 This State Duration

Description

The Module shall have a method for getting the time since the last state change appears.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least one returned duration fits to the current state duration ($\pm 0.05s$).

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.10!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:28,924
Finished-Time:	2025-03-23 14:39:29,176
Time-Consumption	0.252s

Testsummary:

Info	Running state machine test sequence.
Success	Return Value of this_state_duration() is correct (Content 0.25109267234802246 in [0.2 ... 0.3] and Type is <class 'float'>).

3.3.4 Last Transition Condition

Description

The Module shall have a method for getting the last transition condition.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least one returned transition condition fits to the expectation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.11!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:29,177
Finished-Time:	2025-03-23 14:39:29,179
Time-Consumption	0.002s

Testsummary:

Info	Running state machine test sequence.
Success	Returnvalue of last_transition_condition() is correct (Content 'condition_a' and Type is <class 'str'>).

3.3.5 Last Transition Condition was

Description

The Module shall have a method for checking if the given condition was the last transition condition.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least two calls with different return values fit to the expectation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.12!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:29,180
Finished-Time:	2025-03-23 14:39:29,182
Time-Consumption	0.002s

Testsummary:

Info	Running state machine test sequence.
Success	Returnvalue of last_transition_condition(condition_a) is correct (Content True and Type is <class 'bool'>).
Success	Returnvalue of last_transition_condition(condition_c) is correct (Content False and Type is <class 'bool'>).

3.3.6 Previous State

Description

The Module shall have a method for getting the previous state.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least one returned state fits to the expectation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.13!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:29,182

Finished-Time: 2025-03-23 14:39:29,183
 Time-Consumption 0.001s

Testsummary:

Info Running state machine test sequence.
Success Returnvalue of previous_state() is correct (Content 'state_a' and Type is <class 'str'>).

3.3.7 Previous State was

Description

The Module shall have a method for checking if the given state was the previous state.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least two calls with different return values fit to the expectation.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.14!

Testrun: python 3.11.2 (final)
 Caller: /home/dirk/my_repositories/unittest/state_machine/unittest/src/report/_init_.py (323)
 Start-Time: 2025-03-23 14:39:29,184
 Finished-Time: 2025-03-23 14:39:29,186
 Time-Consumption 0.002s

Testsummary:

Info Running state machine test sequence.
Success Returnvalue of previous_state_was(state_a) is correct (Content True and Type is <class 'bool'>).
Success Returnvalue of previous_state_was(state_b) is correct (Content False and Type is <class 'bool'>).

3.3.8 Previous State Duration

Description

The Module shall have a method for getting active time for the previous state.

Reason for the implementation

Comfortable user interface.

Fitcriterion

At least one returned duration fits to the previous state duration ($\pm 0.05s$).

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.15!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:29,186
Finished-Time:	2025-03-23 14:39:29,939
Time-Consumption	0.752s

Testsummary:

Info	Running state machine test sequence.
Success	Return Value of previous.state.duration() is correct (Content 0.7509410381317139 in [0.7 ... 0.8] and Type is <class 'float'>).

3.4 Transition Callbacks

3.4.1 State change callback for a defined transition and targetstate

Description

The state machine shall call all registered methods in the same order like the registration with all user given arguments for a defined set of *transition_condition* and *target_state*.

Reason for the implementation

Triggering state change actions for a specific transition condition and targetstate.

Fitcriterion

Methods are called in the registration order after state change with all user given arguments for the defined transition condition and targetstate and at least for one other condition not.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.16!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:29,939
Finished-Time:	2025-03-23 14:39:29,945
Time-Consumption	0.006s

Testsummary:

Info	Running state machine sequence and storing sequence number for each callback
Success	Execution of state machine callback (1) (state_b, condition_a) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.
Success	Execution of state machine callback (2) (state_b, condition_a) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

3.4.2 State change callback for a defined transition

Description

The state machine shall call all registered methods in the same order like the registration with all user given arguments for a defined *transition_condition* and all *target_states*.

Reason for the implementation

Triggering state change actions for a specific transition condition.

Fitcriterion

Methods are called in the registration order after state change with all user given arguments for the defined transition condition and at least for one other transition condition not.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.17!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/__init__.py (323)
Start-Time:	2025-03-23 14:39:29,945
Finished-Time:	2025-03-23 14:39:29,952
Time-Consumption	0.006s

Testsummary:

Info	Running state machine sequence and storing sequence number for each callback
Success	Execution of state machine callback (1) (all_transitions, condition_b) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.
Success	Execution of state machine callback (2) (all_transitions, condition_b) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

3.4.3 State change callback for a defined targetstate

Description

The state machine shall call all registered methods in the same order like the registration with all user given arguments for all *transition_conditions* and a defined *target_state*.

Reason for the implementation

Triggering state change actions for a specific targetstate.

Fitcriterion

Methods are called in the registration order after state change with the defined targetstate and at least for one other targetstate not.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.18!

Testrun: python 3.11.2 (final)
 Caller: /home/dirk/my_repositories/unittest/state_machine/unittest/src/report/_init_.py (323)
 Start-Time: 2025-03-23 14:39:29,952
 Finished-Time: 2025-03-23 14:39:29,959
 Time-Consumption 0.006s

Testsummary:

Info Running state machine sequence and storing sequence number for each callback
Success Execution of state machine callback (1) (state_b, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.
Success Execution of state machine callback (2) (state_b, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

3.4.4 State change callback for all kind of state changes

Description

The state machine shall call all registered methods in the same order like the registration with all user given arguments for all transitions.

Reason for the implementation

Triggering state change actions for all transition conditions and targetstates.

Fitcriterion

Methods are called in the registration order after state change.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.19!

Testrun: python 3.11.2 (final)
 Caller: /home/dirk/my_repositories/unittest/state_machine/unittest/src/report/_init_.py (323)
 Start-Time: 2025-03-23 14:39:29,959
 Finished-Time: 2025-03-23 14:39:29,969
 Time-Consumption 0.009s

Testsummary:

Info Running state machine sequence and storing sequence number for each callback
Success Execution of state machine callback (1) (all_transitions, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.
Success Execution of state machine callback (2) (all_transitions, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

3.4.5 Execution order of Callbacks

Description

The callbacks shall be executed in the same order as they had been registered.

Reason for the implementation

User shall have the control about the execution order.

Fitcriterion

A callback with specific targetstate and condition will be executed before a non specific callback if the specific one had been registered first.

Testresult

This test was passed with the state: **Success**. See also full trace in section A.1.20!

Testrun:	python 3.11.2 (final)
Caller:	/home/dirk/my_repositories/unittest/state_machine/unittest/src/report/...init...py (323)
Start-Time:	2025-03-23 14:39:29,969
Finished-Time:	2025-03-23 14:39:29,971
Time-Consumption	0.002s

Testsummary:

Success	Callback execution order: Values and number of submitted values is correct. See detailed log for more information.
----------------	--

A Trace for testrun with python 3.11.2 (final)

A.1 Tests with status Info (20)

A.1.1 REQ-0005

Testresult

This test was passed with the state: **Success**.

Info Initialising the state machine with state_c

StateMachine: State change ('__init__'): None -> 'state_c'

Success State after initialisation is correct (Content 'state_c' and Type is <class 'str'>).

Result (State after initialisation): 'state_c' (<class 'str'>)

Expectation (State after initialisation): result = 'state_c' (<class 'str'>)

A.1.2 REQ-0006

Testresult

This test was passed with the state: **Success**.

Info Initialising the state machine with state_c

StateMachine: State change ('__init__'): None -> 'state_c'

Success Last transition condition after initialisation is correct (Content '__init__' and Type is <class 'str'>).

Result (Last transition condition after initialisation): '__init__' (<class 'str'>)

Expectation (Last transition condition after initialisation): result = '__init__' (<class 'str'>)

A.1.3 REQ-0007

Testresult

This test was passed with the state: **Success**.

Info Initialising the state machine with state_c

StateMachine: State change ('__init__'): None -> 'state_c'

Success Last state after initialisation is correct (Content None and Type is <class 'NoneType'>).

Result (Last state after initialisation): None (<class 'NoneType'>)

Expectation (Last state after initialisation): result = None (<class 'NoneType'>)

A.1.4 REQ-0008

Testresult

This test was passed with the state: **Success**.

Info Initialising the state machine with state_c

StateMachine: State change ('__init__'): None -> 'state_c'

Success Keyword argument kw_arg_no.1 stored in state_machine is correct (Content 1 and Type is <class 'int'>).

Result (Keyword argument kw_arg_no.1 stored in state_machine): 1 (<class 'int'>)

Expectation (Keyword argument kw_arg_no.1 stored in state_machine): result = 1 (<class 'int'>)

Success Keyword argument kw_arg_no.2 stored in state_machine is correct (Content '2' and Type is <class 'str'>).

Result (Keyword argument kw_arg_no.2 stored in state_machine): '2' (<class 'str'>)

Expectation (Keyword argument kw_arg_no.2 stored in state_machine): result = '2' (<class 'str'>)
 ↪ 'str'>)

Success Keyword argument kw_arg_no.3 stored in state_machine is correct (Content True and Type is <class 'bool'>).

Result (Keyword argument kw_arg_no.3 stored in state_machine): True (<class 'bool'>)

Expectation (Keyword argument kw_arg_no.3 stored in state_machine): result = True (<class 'bool'>)
 ↪ 'bool'>)

Success Keyword argument kw_arg_no.4 stored in state_machine is correct (Content {'1': 1, '2': 'two'} and Type is <class 'dict'>).

Result (Keyword argument kw_arg_no.4 stored in state_machine): { '1': 1, '2': 'two' } (<class 'dict'>)
 ↪ 'dict'>)

Expectation (Keyword argument kw_arg_no.4 stored in state_machine): result = { '1': 1, '2': 'two' } (<class 'dict'>)
 ↪ 'two' } (<class 'dict'>)

A.1.5 REQ-0017

Testresult

This test was passed with the state: **Success**.

Info Initialising state machine with state_a

StateMachine: State change ('__init__'): None -> 'state_a'

Success Initial state after Initialisation is correct (Content 'state_a' and Type is <class 'str'>).

Result (Initial state after Initialisation): 'state_a' (<class 'str'>)

Expectation (Initial state after Initialisation): result = 'state_a' (<class 'str'>)

Info Work routine executed the 1st time to do the state change. Defined Transitions are: True→state_b (0.0s);
False→state_c (0.0s)

StateMachine: State change ('condition_true'): 'state_a' -> 'state_b'

Success State after 1st execution of work method is correct (Content 'state_b' and Type is <class 'str'>).

Result (State after 1st execution of work method): 'state_b' (<class 'str'>)

Expectation (State after 1st execution of work method): result = 'state_b' (<class 'str'>)

Info Work routine executed the 2nd time to do the state change. Defined Transitions are: False→state_a (0.0s);
True→state_c (0.0s)

StateMachine: State change ('condition_true'): 'state_b' -> 'state_c'

Success State after 2nd execution of work method is correct (Content 'state_c' and Type is <class 'str'>).

Result (State after 2nd execution of work method): 'state_c' (<class 'str'>)

Expectation (State after 2nd execution of work method): result = 'state_c' (<class 'str'>)

Info Work routine executed the 3rd time with no effect. No Transitions starting from state_c (dead end)

Success State after 3rd execution of work method is correct (Content 'state_c' and Type is <class 'str'>).

Result (State after 3rd execution of work method): 'state_c' (<class 'str'>)

Expectation (State after 3rd execution of work method): result = 'state_c' (<class 'str'>)

A.1.6 REQ-0018

Testresult

This test was passed with the state: **Success**.

Info Initialising state machine with state_a

StateMachine: State change ('__init__'): None -> 'state_a'

Success Initial state after Initialisation is correct (Content 'state_a' and Type is <class 'str'>).

Result (Initial state after Initialisation): 'state_a' (<class 'str'>)

Expectation (Initial state after Initialisation): result = 'state_a' (<class 'str'>)

Info Waiting for 0.160s or state change

StateMachine: State change ('condition_true'): 'state_a' -> 'state_b'

Success State after 1st cycle is correct (Content 'state_b' and Type is <class 'str'>).

Result (State after 1st cycle): 'state_b' (<class 'str'>)

Expectation (State after 1st cycle): result = 'state_b' (<class 'str'>)

Success Transition time after 1st cycle is correct (Content 0.15043091773986816 in [0.145 ... 0.155] and Type is <class 'float'>).

Result (Transition time after 1st cycle): 0.15043091773986816 (<class 'float'>)

Expectation (Transition time after 1st cycle): 0.145 <= result <= 0.155

Info Waiting for 0.235s or state change

StateMachine: State change ('condition_true'): 'state_b' -> 'state_c'

Success State after 2nd cycle is correct (Content 'state_c' and Type is <class 'str'>).

Result (State after 2nd cycle): 'state_c' (<class 'str'>)

Expectation (State after 2nd cycle): result = 'state_c' (<class 'str'>)

Success Transition time after 2nd cycle is correct (Content 0.1502208709716797 in [0.145 ... 0.155] and Type is <class 'float'>).

Result (Transition time after 2nd cycle): 0.1502208709716797 (<class 'float'>)

Expectation (Transition time after 2nd cycle): 0.145 <= result <= 0.155

Success Previous state duration is correct (Content 0.22549748420715332 in [0.21999999999999997 ... 0.22999999999999998] and Type is <class 'float'>).

Result (Previous state duration): 0.22549748420715332 (<class 'float'>)

Expectation (Previous state duration): 0.21999999999999997 <= result <= 0.22999999999999998

A.1.7 REQ-0019

Testresult

This test was passed with the state: **Success**.

Info Initialising state machine with state_a, a transition to state_b after 0.151s and a transition to state_c after 0.150s

StateMachine: State change ('__init__'): None -> 'state_a'

Success Initial state after Initialisation is correct (Content 'state_a' and Type is <class 'str'>).

Result (Initial state after Initialisation): 'state_a' (<class 'str'>)

Expectation (Initial state after Initialisation): result = 'state_a' (<class 'str'>)

Info Waiting for 0.300s or state change

Executing method work after 0.000s

Executing method work after 0.060s

Executing method work after 0.121s

Executing method work after 0.182s

StateMachine: State change ('condition_true'): 'state_a' -> 'state_c'

Success State after 1st cycle is correct (Content 'state_c' and Type is <class 'str'>).

Result (State after 1st cycle): 'state_c' (<class 'str'>)

Expectation (State after 1st cycle): result = 'state_c' (<class 'str'>)

A.1.8 REQ-0009

Testresult

This test was passed with the state: **Success**.

Info Initialising the state machine with state_c

StateMachine: State change ('__init__'): None -> 'state_c'

Success Returnvalue of this_state() is correct (Content 'state_c' and Type is <class 'str'>).

Result (Returnvalue of this_state()): 'state_c' (<class 'str'>)

Expectation (Returnvalue of this_state()): result = 'state_c' (<class 'str'>)

A.1.9 REQ-0010

Testresult

This test was passed with the state: **Success**.

Info Initialising the state machine with state_c

StateMachine: State change ('__init__'): None -> 'state_c'

Success Returnvalue of this_state_is(state_c) is correct (Content True and Type is <class 'bool'>).

Result (Returnvalue of this_state_is(state_c)): True (<class 'bool'>)

Expectation (Returnvalue of this_state_is(state_c)): result = True (<class 'bool'>)

Success Returnvalue of this_state_is(state_b) is correct (Content False and Type is <class 'bool'>).

Result (Returnvalue of this_state_is(state_b)): False (<class 'bool'>)

Expectation (Returnvalue of this_state_is(state_b)): result = False (<class 'bool'>)

A.1.10 REQ-0011

Testresult

This test was passed with the state: **Success**.

Info Running state machine test sequence.

StateMachine: State change ('__init__'): None -> 'state_a'

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Waiting for 0.25s

Success Return Value of this_state_duration() is correct (Content 0.25109267234802246 in [0.2 ... 0.3] and Type is <class 'float'>).

Result (Return Value of this_state_duration()): 0.25109267234802246 (<class 'float'>)

Expectation (Return Value of this_state_duration()): 0.2 <= result <= 0.3

A.1.11 REQ-0012

Testresult

This test was passed with the state: **Success**.

Info Running state machine test sequence.

StateMachine: State change ('__init__'): None -> 'state_a'

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Success Returnvalue of last_transition_condition() is correct (Content 'condition_a' and Type is <class 'str'>).

Result (Returnvalue of last_transition_condition()): 'condition_a' (<class 'str'>)

Expectation (Returnvalue of last_transition_condition()): result = 'condition_a' (<class 'str'>)

A.1.12 REQ-0013

Testresult

This test was passed with the state: **Success**.

Info Running state machine test sequence.

StateMachine: State change ('__init__'): None -> 'state_a'

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Success Returnvalue of last_transition_condition(condition_a) is correct (Content True and Type is <class 'bool'>).

Result (Returnvalue of last_transition_condition(condition_a)): True (<class 'bool'>)

```
Expectation (Returnvalue of last_transition_condition(condition_a)): result = True (<class
↳ 'bool'>)
```

Success Returnvalue of last_transition_condition(condition_c) is correct (Content False and Type is <class 'bool'>).

```
Result (Returnvalue of last_transition_condition(condition_c)): False (<class 'bool'>)
```

```
Expectation (Returnvalue of last_transition_condition(condition_c)): result = False (<class
↳ 'bool'>)
```

A.1.13 REQ-0014

Testresult

This test was passed with the state: **Success**.

Info Running state machine test sequence.

```
StateMachine: State change ('__init__'): None -> 'state_a'
```

```
StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'
```

Success Returnvalue of previous_state() is correct (Content 'state_a' and Type is <class 'str'>).

```
Result (Returnvalue of previous_state()): 'state_a' (<class 'str'>)
```

```
Expectation (Returnvalue of previous_state()): result = 'state_a' (<class 'str'>)
```

A.1.14 REQ-0015

Testresult

This test was passed with the state: **Success**.

Info Running state machine test sequence.

```
StateMachine: State change ('__init__'): None -> 'state_a'
```

```
StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'
```

Success Returnvalue of previous_state_was(state_a) is correct (Content True and Type is <class 'bool'>).

```
Result (Returnvalue of previous_state_was(state_a)): True (<class 'bool'>)
```

```
Expectation (Returnvalue of previous_state_was(state_a)): result = True (<class 'bool'>)
```

Success Returnvalue of previous_state_was(state_b) is correct (Content False and Type is <class 'bool'>).

```
Result (Returnvalue of previous_state_was(state_b)): False (<class 'bool'>)
```

```
Expectation (Returnvalue of previous_state_was(state_b)): result = False (<class 'bool'>)
```

A.1.15 REQ-0016

Testresult

This test was passed with the state: **Success**.

Info Running state machine test sequence.

StateMachine: State change ('__init__'): None -> 'state_a'

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Waiting for 0.75s

StateMachine: State change ('condition_b'): 'state_b' -> 'state_a'

Success Return Value of previous.state_duration() is correct (Content 0.7509410381317139 in [0.7 ... 0.8] and Type is <class 'float'>).

Result (Return Value of previous_state_duration()): 0.7509410381317139 (<class 'float'>)

Expectation (Return Value of previous_state_duration()): 0.7 <= result <= 0.8

A.1.16 REQ-0001

Testresult

This test was passed with the state: **Success**.

Info Running state machine sequence and storing sequence number for each callback

StateMachine: State change ('__init__'): None -> 'state_a'

Increasing sequence number to 1 caused by sequence progress

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Executing callback 0 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 2 caused by callback_execution

Executing callback 1 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 3 caused by callback_execution

Increasing sequence number to 4 caused by sequence progress

StateMachine: State change ('condition_b'): 'state_b' -> 'state_a'

Increasing sequence number to 5 caused by sequence progress

StateMachine: State change ('condition_b'): 'state_a' -> 'state_b'

Increasing sequence number to 6 caused by sequence progress

StateMachine: State change ('condition_c'): 'state_b' -> 'state_c'

Success Execution of state machine callback (1) (state_b, condition_a) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

Result (Execution of state machine callback (1) (state_b, condition_a) identified by a ↵ sequence number): [1] (<class 'list'>)

Expectation (Execution of state machine callback (1) (state_b, condition_a) identified by a
 ↪ sequence number): result = [1] (<class 'list'>)

Result (Submitted value number 1): 1 (<class 'int'>)

Expectation (Submitted value number 1): result = 1 (<class 'int'>)

Submitted value number 1 is correct (Content 1 and Type is <class 'int'>).

Success Execution of state machine callback (2) (state_b, condition_a) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

Result (Execution of state machine callback (2) (state_b, condition_a) identified by a
 ↪ sequence number): [2] (<class 'list'>)

Expectation (Execution of state machine callback (2) (state_b, condition_a) identified by a
 ↪ sequence number): result = [2] (<class 'list'>)

Result (Submitted value number 1): 2 (<class 'int'>)

Expectation (Submitted value number 1): result = 2 (<class 'int'>)

Submitted value number 1 is correct (Content 2 and Type is <class 'int'>).

A.1.17 REQ-0002

Testresult

This test was passed with the state: **Success**.

Info Running state machine sequence and storing sequence number for each callback

StateMachine: State change ('__init__'): None -> 'state_a'

Increasing sequence number to 1 caused by sequence progress

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Increasing sequence number to 2 caused by sequence progress

StateMachine: State change ('condition_b'): 'state_b' -> 'state_a'

Executing callback 0 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 3 caused by callback_execution

Executing callback 1 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 4 caused by callback_execution

Increasing sequence number to 5 caused by sequence progress

StateMachine: State change ('condition_b'): 'state_a' -> 'state_b'

Executing callback 0 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 6 caused by callback_execution

Executing callback 1 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 7 caused by callback_execution

Increasing sequence number to 8 caused by sequence progress

StateMachine: State change ('condition_c'): 'state_b' -> 'state_c'

Success Execution of state machine callback (1) (all_transitions, condition_b) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

Result (Execution of state machine callback (1) (all_transitions, condition_b) identified by ↪ a sequence number): [2, 5] (<class 'list'>)

Expectation (Execution of state machine callback (1) (all_transitions, condition_b) ↪ identified by a sequence number): result = [2, 5] (<class 'list'>)

Result (Submitted value number 1): 2 (<class 'int'>)

Expectation (Submitted value number 1): result = 2 (<class 'int'>)

Submitted value number 1 is correct (Content 2 and Type is <class 'int'>).

Result (Submitted value number 2): 5 (<class 'int'>)

Expectation (Submitted value number 2): result = 5 (<class 'int'>)

Submitted value number 2 is correct (Content 5 and Type is <class 'int'>).

Success Execution of state machine callback (2) (all_transitions, condition_b) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

Result (Execution of state machine callback (2) (all_transitions, condition_b) identified by ↪ a sequence number): [3, 6] (<class 'list'>)

Expectation (Execution of state machine callback (2) (all_transitions, condition_b) ↪ identified by a sequence number): result = [3, 6] (<class 'list'>)

Result (Submitted value number 1): 3 (<class 'int'>)

Expectation (Submitted value number 1): result = 3 (<class 'int'>)

Submitted value number 1 is correct (Content 3 and Type is <class 'int'>).

Result (Submitted value number 2): 6 (<class 'int'>)

Expectation (Submitted value number 2): result = 6 (<class 'int'>)

Submitted value number 2 is correct (Content 6 and Type is <class 'int'>).

A.1.18 REQ-0003

Testresult

This test was passed with the state: **Success**.

Info Running state machine sequence and storing sequence number for each callback

StateMachine: State change ('__init__'): None -> 'state_a'

Increasing sequence number to 1 caused by sequence progress

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Executing callback 0 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 2 caused by callback_execution

Executing callback 1 - tests.test_callbacks.exec_with_counter

Increasing sequence number to 3 caused by callback_execution

Increasing sequence number to 4 caused by sequence progress

```

StateMachine: State change ('condition_b'): 'state_b' -> 'state_a'
Increasing sequence number to 5 caused by sequence progress
StateMachine: State change ('condition_b'): 'state_a' -> 'state_b'
Executing callback 0 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 6 caused by callback_execution
Executing callback 1 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 7 caused by callback_execution
Increasing sequence number to 8 caused by sequence progress
StateMachine: State change ('condition_c'): 'state_b' -> 'state_c'

```

Success Execution of state machine callback (1) (state_b, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

```

Result (Execution of state machine callback (1) (state_b, all_conditions) identified by a
↳ sequence number): [ 1, 5 ] (<class 'list'>)
Expectation (Execution of state machine callback (1) (state_b, all_conditions) identified by
↳ a sequence number): result = [ 1, 5 ] (<class 'list'>)
Result (Submitted value number 1): 1 (<class 'int'>)
Expectation (Submitted value number 1): result = 1 (<class 'int'>)
Submitted value number 1 is correct (Content 1 and Type is <class 'int'>).
Result (Submitted value number 2): 5 (<class 'int'>)
Expectation (Submitted value number 2): result = 5 (<class 'int'>)
Submitted value number 2 is correct (Content 5 and Type is <class 'int'>).

```

Success Execution of state machine callback (2) (state_b, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

```

Result (Execution of state machine callback (2) (state_b, all_conditions) identified by a
↳ sequence number): [ 2, 6 ] (<class 'list'>)
Expectation (Execution of state machine callback (2) (state_b, all_conditions) identified by
↳ a sequence number): result = [ 2, 6 ] (<class 'list'>)
Result (Submitted value number 1): 2 (<class 'int'>)
Expectation (Submitted value number 1): result = 2 (<class 'int'>)
Submitted value number 1 is correct (Content 2 and Type is <class 'int'>).
Result (Submitted value number 2): 6 (<class 'int'>)
Expectation (Submitted value number 2): result = 6 (<class 'int'>)
Submitted value number 2 is correct (Content 6 and Type is <class 'int'>).

```

A.1.19 REQ-0004

Testresult

This test was passed with the state: **Success**.

Info Running state machine sequence and storing sequence number for each callback

```

StateMachine: State change ('__init__'): None -> 'state_a'

```

```

Increasing sequence number to 1 caused by sequence progress
StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'
Executing callback 0 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 2 caused by callback_execution
Executing callback 1 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 3 caused by callback_execution
Increasing sequence number to 4 caused by sequence progress
StateMachine: State change ('condition_b'): 'state_b' -> 'state_a'
Executing callback 0 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 5 caused by callback_execution
Executing callback 1 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 6 caused by callback_execution
Increasing sequence number to 7 caused by sequence progress
StateMachine: State change ('condition_b'): 'state_a' -> 'state_b'
Executing callback 0 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 8 caused by callback_execution
Executing callback 1 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 9 caused by callback_execution
Increasing sequence number to 10 caused by sequence progress
StateMachine: State change ('condition_c'): 'state_b' -> 'state_c'
Executing callback 0 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 11 caused by callback_execution
Executing callback 1 - tests.test_callbacks.exec_with_counter
Increasing sequence number to 12 caused by callback_execution

```

Success Execution of state machine callback (1) (all_transitions, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

```

Result (Execution of state machine callback (1) (all_transitions, all_conditions) identified
↳ by a sequence number): [ 1, 4, 7, 10 ] (<class 'list'>)
Expectation (Execution of state machine callback (1) (all_transitions, all_conditions)
↳ identified by a sequence number): result = [ 1, 4, 7, 10 ] (<class 'list'>)
Result (Submitted value number 1): 1 (<class 'int'>)
Expectation (Submitted value number 1): result = 1 (<class 'int'>)
Submitted value number 1 is correct (Content 1 and Type is <class 'int'>).
Result (Submitted value number 2): 4 (<class 'int'>)
Expectation (Submitted value number 2): result = 4 (<class 'int'>)
Submitted value number 2 is correct (Content 4 and Type is <class 'int'>).
Result (Submitted value number 3): 7 (<class 'int'>)
Expectation (Submitted value number 3): result = 7 (<class 'int'>)
Submitted value number 3 is correct (Content 7 and Type is <class 'int'>).
Result (Submitted value number 4): 10 (<class 'int'>)
Expectation (Submitted value number 4): result = 10 (<class 'int'>)

```

Submitted value number 4 is correct (Content 10 and Type is <class 'int'>).

Success Execution of state machine callback (2) (all_transitions, all_conditions) identified by a sequence number: Values and number of submitted values is correct. See detailed log for more information.

Result (Execution of state machine callback (2) (all_transitions, all_conditions) identified by a sequence number): [2, 5, 8, 11] (<class 'list'>)

Expectation (Execution of state machine callback (2) (all_transitions, all_conditions) identified by a sequence number): result = [2, 5, 8, 11] (<class 'list'>)

Result (Submitted value number 1): 2 (<class 'int'>)

Expectation (Submitted value number 1): result = 2 (<class 'int'>)

Submitted value number 1 is correct (Content 2 and Type is <class 'int'>).

Result (Submitted value number 2): 5 (<class 'int'>)

Expectation (Submitted value number 2): result = 5 (<class 'int'>)

Submitted value number 2 is correct (Content 5 and Type is <class 'int'>).

Result (Submitted value number 3): 8 (<class 'int'>)

Expectation (Submitted value number 3): result = 8 (<class 'int'>)

Submitted value number 3 is correct (Content 8 and Type is <class 'int'>).

Result (Submitted value number 4): 11 (<class 'int'>)

Expectation (Submitted value number 4): result = 11 (<class 'int'>)

Submitted value number 4 is correct (Content 11 and Type is <class 'int'>).

A.1.20 REQ-0020

Testresult

This test was passed with the state: **Success**.

Success Callback execution order: Values and number of submitted values is correct. See detailed log for more information.

StateMachine: State change ('__init__'): None -> 'state_a'

StateMachine: State change ('condition_a'): 'state_a' -> 'state_b'

Executing callback 0 - unittest.test.report_value

Executing callback 2 - unittest.test.report_value

StateMachine: State change ('condition_b'): 'state_b' -> 'state_a'

Executing callback 1 - unittest.test.report_value

Executing callback 2 - unittest.test.report_value

Result (Callback execution order): ['specific callback for reaching state_b', 'nonspecific callback', 'specific callback for reaching state_a', 'nonspecific callback'] (<class 'list'>)

Expectation (Callback execution order): result = ['specific callback for reaching state_b', 'nonspecific callback', 'specific callback for reaching state_a', 'nonspecific callback'] (<class 'list'>)

Result (Submitted value number 1): 'specific callback for reaching state_b' (<class 'str'>)


```
Expectation (Submitted value number 1): result = 'specific callback for reaching state_b'
↳ (<class 'str'>)
```

```
Submitted value number 1 is correct (Content 'specific callback for reaching state_b' and
↳ Type is <class 'str'>).
```

```
Result (Submitted value number 2): 'nonspecific callback' (<class 'str'>)
```

```
Expectation (Submitted value number 2): result = 'nonspecific callback' (<class 'str'>)
```

```
Submitted value number 2 is correct (Content 'nonspecific callback' and Type is <class
↳ 'str'>).
```

```
Result (Submitted value number 3): 'specific callback for reaching state_a' (<class 'str'>)
```

```
Expectation (Submitted value number 3): result = 'specific callback for reaching state_a'
↳ (<class 'str'>)
```

```
Submitted value number 3 is correct (Content 'specific callback for reaching state_a' and
↳ Type is <class 'str'>).
```

```
Result (Submitted value number 4): 'nonspecific callback' (<class 'str'>)
```

```
Expectation (Submitted value number 4): result = 'nonspecific callback' (<class 'str'>)
```

```
Submitted value number 4 is correct (Content 'nonspecific callback' and Type is <class
↳ 'str'>).
```

B Test-Coverage

B.1 state_machine

The line coverage for state_machine was 100.0%

The branch coverage for state_machine was 100.0%

B.1.1 state_machine.__init__.py

The line coverage for state_machine.__init__.py was 100.0%

The branch coverage for state_machine.__init__.py was 100.0%

```
1 #!/usr/bin/env python
2 # -*- coding: utf-8 -*-
3 #
4 """
5 state_machine (State Machine)
6 =====
7
8 **Author:**
9
10 * Dirk Alders <sudo-dirk@mount-mockery.de>
11
12 **Description:**
13
14     This Module helps implementing state machines.
15
16 **Submodules:**
17
18 * :class:`state_machine.state_machine`
19
20 **Unittest:**
```

Unittest for state_machine

```
21
22     See also the :download:`unittest <state_machine/_testresults_/unittest.pdf>` documentation.
23
24 **Module Documentation:**
25
26 """
27 __DEPENDENCIES__ = []
28
29 import logging
30 import time
31
32
33 try:
34     from config import APP_NAME as ROOT_LOGGER_NAME
35 except ImportError:
36     ROOT_LOGGER_NAME = 'root'
37 logger = logging.getLogger(ROOT_LOGGER_NAME).getChild(__name__)
38
39
40 __INTERPRETER__ = (3, )
41 """The supported Interpreter-Versions"""
42 __DESCRIPTION__ = """This Module helps implementing state machines."""
43 """The Module description"""
44
45
46 class state_machine(object):
47     """
48         :param default_state: The default state which is set on initialisation.
49         :param log_lvl: The log level, this Module logs to (see Logging-Levels of Module :mod:`logging`
50         `)
51
52         .. note:: Additional keyword parameters will be stored as variables of the instance (e.g. to
53         give variables or methods for transition condition calculation).
54
55         A state machine class can be created by deriving it from this class. The transitions are
56         defined by overriding the variable `TRANSITIONS`.
57         This Variable is a dictionary, where the key is the start-state and the content is a tuple or
58         list of transitions. Each transition is a tuple or list
59         including the following information: (condition-method (str), transition-time (number),
60         target_state (str)).
61
62         .. note:: The condition-method needs to be implemented as part of the new class.
63
64         .. note:: It is usefull to define the states as variables of this class.
65
66         **Example:**
67
68         .. literalinclude:: state_machine/_examples_/example.py
69
70         .. literalinclude:: state_machine/_examples_/example.log
71         """
72         TRANSITIONS = {}
73         LOG_PREFIX = 'StateMachine:'
74
75         def __init__(self, default_state, log_lvl, **kwargs):
76             self.__state__ = None
77             self.__last_transition_condition__ = None
78             self.__conditions_start_time__ = {}
79             self.__state_change_callbacks__ = {}
80             self.__log_lvl__ = log_lvl
81             self.__set_state__(default_state, '__init__')
82             self.__callback_id__ = 0
83             for key in kwargs:
84                 setattr(self, key, kwargs.get(key))
```

Unittest for state_machine

```
81
82 def register_state_change_callback(self, state, condition, callback, *args, **kwargs):
83     """
84     :param state: The target state. The callback will be executed, if the state machine
85     changes to this state. None means all states.
86     :type state: str
87     :param condition: The transition condition. The callback will be executed, if this
88     condition is responsible for the state change. None means all conditions.
89     :type condition: str
90     :param callback: The callback to be executed.
91
92     .. note:: Additional arguments and keyword parameters are supported. These arguments and
93     parameters will be used as arguments and parameters for the callback execution.
94
95     This methods allows to register callbacks which will be executed on state changes.
96     """
97     if state not in self.__state_change_callbacks__:
98         self.__state_change_callbacks__[state] = {}
99     if condition not in self.__state_change_callbacks__[state]:
100         self.__state_change_callbacks__[state][condition] = []
101     self.__state_change_callbacks__[state][condition].append((self.__callback_id__, callback,
102     args, kwargs))
103     self.__callback_id__ += 1
104
105 def this_state(self):
106     """
107     :return: The current state.
108
109     This method returns the current state of the state machine.
110     """
111     return self.__state__
112
113 def this_state_is(self, state):
114     """
115     :param state: The state to be checked
116     :type state: str
117     :return: True if the given state is currently active, else False.
118     :rtype: bool
119
120     This methods returns the boolean information if the state machine is currently in the
121     given state.
122     """
123     return self.__state__ == state
124
125 def this_state_duration(self):
126     """
127     :return: The time how long the current state is active.
128     :rtype: float
129
130     This method returns the time how long the current state is active.
131     """
132     return time.time() - self.__time_stamp_state_change__
133
134 def last_transition_condition(self):
135     """
136     :return: The last transition condition.
137     :rtype: str
138
139     This method returns the last transition condition.
140     """
141     return self.__last_transition_condition__
```

Unittest for state_machine

```

138 def last_transition_condition_was(self, condition):
139     """
140     :param condition: The condition to be checked
141     :type condition: str
142     :return: True if the given condition was the last transition condition, else False.
143     :rtype: bool
144
145     This methods returns the boolean information if the last transition condition is
146     equivalent to the given condition.
147     """
148     return self.__last_transition_condition__ == condition
149
150 def previous_state(self):
151     """
152     :return: The previous state.
153     :rtype: str
154
155     This method returns the previous state of the state machine.
156     """
157     return self.__prev_state__
158
159 def previous_state_was(self, state):
160     """
161     :param state: The state to be checked
162     :type state: str
163     :return: True if the given state was previously active, else False.
164     :rtype: bool
165
166     This methods returns the boolean information if the state machine was previously in the
167     given state.
168     """
169     return self.__prev_state__ == state
170
171 def previous_state_duration(self):
172     """
173     :return: The time how long the previous state was active.
174     :rtype: float
175
176     This method returns the time how long the previous state was active.
177     """
178     return self.__prev_state_dt__
179
180 def __set_state__(self, target_state, condition):
181     logger.log(self.__log_lvl__, "%s State change (%s): %s -> %s", self.LOG_PREFIX, repr(
182     condition), repr(self.__state__), repr(target_state))
183     timestamp = time.time()
184     self.__prev_state__ = self.__state__
185     if self.__prev_state__ is None:
186         self.__prev_state_dt__ = 0.
187     else:
188         self.__prev_state_dt__ = timestamp - self.__time_stamp_state_change__
189     self.__state__ = target_state
190     self.__last_transition_condition__ = condition
191     self.__time_stamp_state_change__ = timestamp
192     self.__conditions_start_time__ = {}
193     # Callback collect
194     this_state_change_callbacks = []
195     this_state_change_callbacks.extend(self.__state_change_callbacks__.get(None, {}).get(None
196     , []))
197     this_state_change_callbacks.extend(self.__state_change_callbacks__.get(target_state, {}).
198     get(None, []))
199     this_state_change_callbacks.extend(self.__state_change_callbacks__.get(None, {}).get(
200     condition, []))
201     this_state_change_callbacks.extend(self.__state_change_callbacks__.get(target_state, {}).
202     get(condition, []))

```

Unittest for state_machine

```
196     # Callback sorting
197     this_state_change_callbacks.sort()
198     # Callback execution
199     for cid, callback, args, kwargs in this_state_change_callbacks:
200         logger.debug('Executing callback %d - %s.%s', cid, callback.__module__, callback.
201             __name__)
202         callback(*args, **kwargs)
203
204     def work(self):
205         """
206         This Method needs to be executed cyclicly to enable the state machine.
207         """
208         tm = time.time()
209         transitions = self.TRANSITIONS.get(self.this_state())
210         if transitions is not None:
211             active_transitions = []
212             cnt = 0
213             for method_name, transition_delay, target_state in transitions:
214                 method = getattr(self, method_name)
215                 if method():
216                     if method_name not in self.__conditions_start_time__:
217                         self.__conditions_start_time__[method_name] = tm
218                     if tm - self.__conditions_start_time__[method_name] >= transition_delay:
219                         active_transitions.append((transition_delay - tm + self.
220                             __conditions_start_time__[method_name], cnt, target_state, method_name))
221                 else:
222                     self.__conditions_start_time__[method_name] = tm
223             cnt += 1
224             if len(active_transitions) > 0:
225                 active_transitions.sort()
226                 self.__set_state__(active_transitions[0][2], active_transitions[0][3])
```